

LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 NW 1/4 Section Number 4 Township Number T 27 S Range Number R 1 E
 County: SEDGWICK

Distance and direction from nearest town or city street address of well if located within city?

100' E of 29th & Emporia

WND-12D

WATER WELL OWNER: Coleman Company (Ferrotech Foundry)

IR#, St. Address, Box #: 25D N. St. Francis


Board of Agriculture, Division of Water Resources

City, State, ZIP Code: Wichita, KS 67202

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL: 46 ft. ELEVATION:



Depth(s) Groundwater Encountered: 13 ft. 2. 13 ft. 3. 8/12/92 ft.

WELL'S STATIC WATER LEVEL: 13.30 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 7 1/4 in. to 46 ft. after 13 hours pumping 13 gpm

Est. Yield 7 1/4 gpm: Well water was 7 1/4 in. to 46 ft. after 13 hours pumping 13 gpm

Bore Hole Diameter: 7 1/4 in. to 46 ft. and 13 in. to 46 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued X Clamped X

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded X

2 PVC

4 ABS

7 Fiberglass

Threaded X

Blank casing diameter: 2 in. to 36 ft. Dia. Sch 40 in. to 46 ft. Dia. 40 in. to 46 ft.

Casing height above land surface: 2 in., weight Sch 40 lbs./ft. Wall thickness or gauge No. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

8 RMP (SR)

10 Asbestos-cement

11 Other (specify)

2 Brass

4 Galvanized steel

6 Concrete tile

9 ABS

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 36 ft. to 46 ft. From 36 ft. to 46 ft.

From 31 ft. to 46 ft. From 31 ft. to 46 ft.

GRAVEL PACK INTERVALS: From 31 ft. to 46 ft. From 31 ft. to 46 ft.

From 31 ft. to 46 ft. From 31 ft. to 46 ft.

GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 0 ft. to 31 ft. From 0 ft. to 31 ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

North

How many feet?

28'

FROM 0 TO 13 LITHOLOGIC LOG FROM 0 TO 13 PLUGGING INTERVALS

13 46 Alay 13 46 Sand

46 Shale 46

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/6/92 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 8/12/92

under the business name of Groundwater Technology, Inc. by (signature) Steven R. Mitchell

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department

of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

000097