

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction <u>SW 1/4 NW 1/4 SW 1/4</u>	Section Number <u>4</u>	Township Number <u>T 27 S</u>	Range Number <u>R 1 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>~150' East of 23rd St. & Broadway</u>					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		<u>WNIO - City of Wichita</u> <u>455 N. Main - 13th Floor</u> <u>Wichita KS 67202</u> <u>WNO-13</u> Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>22</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>13.8</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>13.8</u> ft. below land surface measured on mo/day/yr <u>3-27-91</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter <u>7.25</u> in. to <u>22</u> ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2</u> in. to <u>12</u> ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>30</u> in., weight <u>0.7</u> lbs./ft. Wall thickness or gauge No. <u>5-4.40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot <u>0.01</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 12 None used (open hole) SCREEN-PERFORATED INTERVALS: From <u>22</u> ft. to <u>12</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>22</u> ft. to <u>9</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.			
		6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From <u>6.5</u> ft. to <u>Surface</u> ft., From <u>9</u> ft. to <u>6.5</u> ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon <u>11 Fuel storage</u> 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>NW</u> How many feet? <u>900'</u>					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0 6		Sandy CLAY fine sand			
6 9		Silty SAND			
9 11		Sandy CLAY fine sand			
11 22		Silty SAND med to fine w/ some coarse with depth			
		grout variance granted,			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-27-91</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>577</u> This Water Well Record was completed on (mo/day/yr) <u>4/22/91</u> under the business name of <u>Groundwater Technology</u> by (signature) <u>Albert Stout</u>					