		ATER WELL RECORD	Form WWC-5	KSA 82a-1	212 RW #3	
LOCATION OF W	ATER WELL: Fraction	Near Center of	S ¹ ₂ Sec	ction Number	Township Number	Range Number
ounty: Sedgw:	THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TW		E 1/4	4	<u>T 27 S</u>	R 1 (E)W
	on from nearest town or city stre		d within city?			
	and & 21st in Wichi				 	
WATER WELL C		-			1 of a batt	ery of 3 b, Division of Water Resources
R#, St. Address, I						_ •
ty, State, ZIP Cod			26 5		Application Number	
AN "X" IN SECT	LOCATION WITH 4 DEPTH CON BOX: Depth(s) Gro					3
Ī	WELL'S STA	ATIC WATER LEVEL1	4.1 ft. b	elow land surfa	ce measured on mo/day/	yr10/25/88
	<u> </u>	Pump test data: Well water	erwas	ft. afte	er hours	pumping gpm
NW -	Est. Yield	gpm: Well wate	erwas	ft. afte	er hours	pumping gpm
w L	Bore Hole D	iameter 22 in. to	26 . 5	ft., ar	nd	in. toft.
w i	I WELL WATE	ER TO BE USED AS:	5 Public water		Air conditioning 1	
w	1 Dome	estic 3 Feedlot	6 Oil field wa	ter supply 9	Dewatering (1	2)Other (Specify below)
- 3" -	2 Imigati	ion 4 Industrial	7 Lawn and g	garden only 10	Observation well	Recovery.Well
	1 X Was a chemi	ical/bacteriological sample	submitted to De	epartment? Yes	; If y	es, mo/day/yr sample was sub-
	\$ mitted			Wate	r Well Disinfected? Yes	X No
TYPE OF BLANK	CASING USED:	5 Wrought iron	8 Concre	ete tile	CASING JOINTS: GIL	ied Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other	(specify below)		elded
2 PVC	4 ABS	7 Fiberglass		·····		Slip w/screws
	er					
sing height above	land surface3.5 Below	\dots in., weight \dots 1	7.05	lbs./ft.	Wall thickness or gauge	No 6.87
PE OF SCREEN	OR PERFORATION MATERIAL	:	7 PV		10 Asbestos-cer	
1 Steel	3 Stainless steel	5 Fiberglass		IP (SR)	11 Other (speci	y)
2 Brass	4 Galvanized steel	6 Concrete tile	9 AB		12 None used (open hole)
REEN OR PERF	DRATION OPENINGS ARE:	5 Gauz	ed wrapped		8 Saw cut	11 None (open hole)
1 Continuous	slot 3 Mill slot	6 Wire	wrapped		9 Drilled holes	
2 Louvered sh	, , ,	7 Torch	cut :			
REEN-PERFORA	TED INTERVALS: From	7.•5 ft. to	17.5	ft., From	ft	. to
						toft.
GRAVEL F	ACK INTERVALS: From	21.5 ft. to	26.5	ft., From	5,5 ft	toft.
	From	19.5 ft. to 2	1.5-Bento	nite Plug	ft	to ft.
GROUT MATERI	AL: 1 Neat cement	2 Cement grout	3 Bento	nite 4 O	ther	
	om 0 ft. to		• 5 ft.	to	ft., From	ft. toft.
at is the nearest	source of possible contamination	n:		10 Livesto	ck pens 14	Abandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy		11 Fuel st	orage 15	Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lage	oon	12 Fertilize	_	Other (specify below)
3 Watertight se	wer lines 6 Seepage pit			13 Insection	ide storage	
ection from well?	Within the immedia			How many		
ROM TO	LITHOLOG		FROM	то	LITHOLO	OGIC LOG
0 2.5	Fill dirt.					
2.5 8	Sand.					
8 15	Blue clay.	· .				
15 34	Sand fine to me	dium coarse. Sma	11			
	gravel.					
34 35.5	Brown clay.					
35.5 36	Shale.			-		
	· · · · · · · · · · · · · · · · · · ·			1.0		
	<u> </u>					
			` _			
CONTRACTOR'S	OR LANDOWNER'S CERTIFIC	ATION: This water well w	es (1) constru	oted (2) recons	structed or (3) plugged u	nder my juriediction and was
	7 0 /7 7 / 0 0					nowledge and belief. Kansas
	pr's License No145					_
	ame of Henkle Drilling					
NSTRUCTIONS: LIE	typewriter or ball point pen. PLEASE F	PRESS FIRM! Yand PRINT des	rly Please fill in I	by (signatur	or circle the correspondence S	end too three copies to Kansas
	and Environment, Bureau of Water Pr					
records.			•			