1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number	
Sedgwick	NE 1/4	SW 1/4 SI	,,		-	10	
			£ 1/4	66	T 27 s	E R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?							
2401 Coolidage	Wichita,						
	MAN, Janet						
RR#, ST. ADRESS, BOX#: 2820 Bentbay Circle Board of Agriculture, Divivsion of Water Resource							
CITY, STATE, ZIP CODE: Wichi	ta, Kansas	PLUGGED			Application Number	;	
3 LOCATE WELL'S LOCATION WITH 4	DEPTH OF COM	PLETED WELL	25	ft. ELE	VATION:		
AN "X" IN SECTION BOX:	Depth(s) groundwar	ter Encountered	1	ft.	2 ft.	3 ft.	
	ELL'S STATIC WA	TER LEVEL 12	FT.	BELOW LAND SUR	FACE MEASURED ON mo/day/yr	07/07/1993	
NW NE	Pump test	data: Well wa	ter was	ft. a	ofter hours pum	ping gpm	
Fet	. Yield	gpm: Well wa	nter was	ft. s	after hours pum	ping gpm	
E Boo	re Hole Diameter WA	c in to	0	ft.,	and in.	to ft.	
= "	WA ELL WATER T O D	E USED AS: 51	Public water	_	8 Air conditioning 11 Ir	ijection well	
	1 Domestic		Oil field wa		•	ther (Specify below)	
	2 Irrigation	4 Industrial 7	Lawn and g		0 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was							
S submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED:		F.W					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (Specify below) Welded							
2 PVC 4 ABS		7 Fiberglass	,	Other (Speeny be	,		
	to			4		A	
DETOM		ft., Dia	in.	to lbs. / ft. V	ft., Dia in.	to ft.	
Casing height ahove land surface 120 TYPE OF SCREEN OR PERFORATIO) in., ON MATERIAL:	weight	7	PVC	Wall thickness or gauge No. 10 Asbestos-ceme	nt	
1 Steel 3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify)		
2 Brass 4 Galvanized steel		6 Concrete tile		ABS	12 None used (op		
2 Company of the last (open last)					11 None (open hole)		
		5 Gauzed wrapped			9 Drilled holes		
o will side		6 Wire wrapped					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATION INTERVAL	S: from	ft. te	0	ft., From	ft. to	ft.	
from		ft. t	0	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from		ft. to		ft., From	ft. to	ft.	
from		ft. to		ft., From	ft. to	ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
	t. to	ft., From	ft.	to	ft., From	ft. to ft.	
What is the nearest source of possible con	ntamination:			10 Livestoc	ek pens 14 A	bandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel sto	130	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertiliz		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well?					How many feet?		
FROM TO LIT	HOLOGIC LOG		FROM	ТО	PLUGGING INTER	RVALS	
			0		ement grout		
			_3	20 E	entonite hole	plug	
			20	25 c	chlorinated sand	d and gravel	
	7				7		
7 002/70 40707							
CONTRACTOR'S OR LANDOWNER'S C	ERTIFICATION: This	water well was (1)	constructe	ed, (2) reconstru	cted, or (3) plugged under m	y jurisdiction and	
was completed on (mo/day/year)							
lucius - Louis Wall C Duma Campina That							
Vama tradarich							
597 yane orientiak							