

LOCATION OF WATER WELL:		Fraction	Pump WWC-3	RSA 62a-1212	Section Number	Township Number	Range Number
County: Sedgewick		SW 1/4 NE 1/4 SE 1/4			7	T 27 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city? 1616 PERRY WICHITA, KANS							
WATER WELL OWNER: DICK SMOLL 1616 PERRY WICHITA KANS				Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :				Application Number: NONE			
City, State, ZIP Code :							
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 31 ft. ELEVATION: 1300 FT.					
		Depth(s) Groundwater Encountered 1. 14 ft. 2. BASEMENT ft. 3. 5-82 ft.					
		WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on mo/day/yr 3-5-82					
		Pump test data: Well water was NA ft. after NA hours pumping NA gpm					
		Est. Yield 75 gpm Well water was NA ft. after NA hours pumping NA gpm					
		Bore Hole Diameter 9 in. to 14 ft., and 6 in. to 31 ft.					
		WELL WATER TO BE USED AS:					
		1 Domestic    3 Feedlot    6 Oil field water supply    9 Dewatering    11 Injection well 2 Irrigation    4 Industrial    ⑦ Lawn and garden only    10 Observation well    12 Other (Specify below)					
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes No					
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped					
1 Steel    ③ RMP (SR)		Welded					
2 PVC    4 ABS		Threaded					
Blank casing diameter 5 in. to 24 ft., Dia		Casing height above land surface 1.59 lbs./ft. Wall thickness or gauge No. 209					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC    10 Asbestos-cement					
1 Steel    3 Stainless steel    5 Fiberglass    ⑧ RMP (SR)		11 Other (specify)					
2 Brass    4 Galvanized steel    6 Concrete tile    9 ABS		12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped    ⑧ Saw cut    11 None (open hole)					
1 Continuous slot    3 Mill slot    6 Wire wrapped    9 Drilled holes		10 Other (specify)					
2 Louvered shutter    4 Key punched    7 Torch cut							
SCREEN-PERFORATED INTERVALS:		From 23 ft. to 31 ft., From ft. to ft.					
GRAVEL PACK INTERVALS:		From ft. to ft., From ft. to ft.					
NONE							
GROUT MATERIAL:		1 Neat cement    ② Cement grout    3 Bentonite    4 Other					
Grout Intervals: From 0 ft. to 14 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens    14 Abandoned water well					
1 Septic tank    4 Lateral lines    7 Pit privy    11 Fuel storage    15 Oil well/Gas well		12 Fertilizer storage    16 Other (specify below)					
② Sewer lines    5 Cess pool    8 Sewage lagoon    13 Insecticide storage							
③ Watertight sewer lines    6 Seepage pit    9 Feedyard							
Direction from well?		How many feet? EAST					
5 FT.							
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG		
0	8	SAND MED-TAN					
8	16	SAND MED-BROKEN					
16	31	SAND COARSE TAN					
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-5-82 and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's License No. 104 This Water Well Record was completed on (mo/day/yr) 4-5-82							
under the business name of BEARDEL Pump & Well by (signature) [Signature]							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							