

1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 NE 1/4 Section Number 8 Township Number T 27 S Range Number R 1 E/W  
 County: SEDG WICK  
 Distance and direction from nearest town or city street address of well if located within city?  
1847 WELLINGTON PLACE, WICHITA, KS

2 WATER WELL OWNER: RON RYAN 800 SHADYWAY  
 RR#, St. Address, Box #: WICHITA, KANS 67203  
 City, State, ZIP Code: WICHITA, KANS 67203  
 Board of Agriculture, Division of Water Resources  
 Application Number: NONE

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	
		X	
E	SW	SE	
S			

4 DEPTH OF COMPLETED WELL 35 ft. ELEVATION: 1300  
 Depth(s) Groundwater Encountered 1. 20 ft. 2. 20 ft. 3. 10-11-82 ft.  
 WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was NA ft. after NA hours pumping NA gpm  
 Est. Yield 70 gpm Well water was NA ft. after NA hours pumping NA gpm  
 Bore Hole Diameter 9 in. to 13 ft. and 6 in. to 35 ft.  
 WELL WATER TO BE USED AS: 5 Public water supply ☒ 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED: 1 Steel ☒ 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: ☒ Glued ☒ Clamped  
 2 PVC ☒ 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing diameter 5 in. to 22 ft. Dia. in. to 209 ft.  
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 209  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass ☒ 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped ☒ 8 Saw cut 11 None (open hole)  
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 21 ft. to 35 ft. From 21 ft. to 35 ft. From 21 ft. to 35 ft. From 21 ft. to 35 ft.  
 GRAVEL PACK INTERVALS: From NONE ft. to NONE ft. From NONE ft. to NONE ft. From NONE ft. to NONE ft. From NONE ft. to NONE ft.

6 GROUT MATERIAL: 1 Neat cement ☒ 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 3 ft. to 13 ft. From 3 ft. to 13 ft. From 3 ft. to 13 ft. From 3 ft. to 13 ft.  
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well  
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)  
☒ 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage  
 Direction from well? NORTH How many feet? 40

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	TOP SOIL BLACK			
3	6	SUB SOIL BROWN			
6	18	SAND TAN MEDIUM			
18	35	SAND COARSE TAN			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-11-82 and this record is true to the best of my knowledge and belief. Kansas  
 Water Well Contractor's License No. 184 This Water Well Record was completed on (mo/day/yr) 10/17/82  
 under the business name of BEARDEN PUMP & WELL by (signature) Otis W. Bearden  
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

27

R

1

BW

SEC.

8

SW

1/4

SE

1/4

NE

1/4