				ER WELL RECORD	Form WWC-5		1			
1 LOCATI County:	, , ,,	TER WELL:	Fraction	NE 14	NE 1/4 Sec	ction Number	Township	Number S	Range Number	
				address of well if loca	ated within city?	4		MW-S	5	
O MATE	R WELL OV			nacis Tr				F100-2		
_					•		Board (of Agriculture [Division of Water Resource	
	Address, Bo , ZIP Code	Wid	nita, K	advay 101	- 410		Applica	ation Number:		
LOCATI	E WELL'S L IN SECTIO	OCATION WITH A	DEPTH OF	COMPLETED WELL.	1 185	ft. ELEVA	TION:		fallaràft	
ŧ [!		WELL'S STAT	IC WATER LEVEL	. 1 6.5 ft. t	pelow land surf	face measured	d on mo/day/yr	////8/89 mping gpi	
-	WW		Est. Yield	gpm: Well w	ater was	ft. af	ter	hours pur	mping gp	
≝ w ⊦	1		Bore Hole Diar	meter છ in.	to 25		and	in.	to	
ž w	!		WELL WATER	TO BE USED AS:	5 Public wate	er supply	8 Air condition	ning 11	Injection well	
7 l	SW	- 5	 Domesti 	ic 3 Feedlot			9 Dewatering		Other (Specify below)	
	1	%	2 Irrigation	n 4 Industrial	7 Lawn and	garden only 🄇	0 Monitoring	well		
l L	i	1	Was a chemica	al/bacteriological samp	le submitted to D	epartment? Ye	sNo.	; If yes,	mo/day/yr sample was so	
<u> </u>		5	mitted			Wat	er Well Disinfe	ected? Yes	No No	
5 TYPE	OF BLANK	CASING USED:		5 Wrought iron	8 Concr	ete tile	CASING	JOINTS: Glued	l Clamped	
1 St	eel	3 RMP (SR	()	6 Asbestos-Ceme	nt 9 Other	(specify below	<i>(</i>)	Welde	ed	
2 P	ری/	A ABS	سر و	7 Fiberglass				Threa	ıded	
Blank casi	ing diameter	· 22- i	n. to 1.5	ft., Dia	in. to بنيان.		ft., Dia		ا به . بورسترير، پسر in. to	
Casing he	ight above I	and surface	<i>(</i> /	in., weight	0.+		t. Wall thickne	ess or gauge No	in to 0.154 in.	
_	_	R PERFORATION			PV			Asbestos-ceme		
1 St	eel	3 Stainless	steel	5 Fiberglass	O RI	MP (SR)	11	Other (specify)		
2 Br	ass	4 Galvanize	ed steel	6 Concrete tile	9 AE		12	None used (op	en hole)	
SCREEN	OR PERFO	RATION OPENING	S ARE:	5 Ga	uzed wrapped		8 Saw cut		11 None (open hole)	
	ontinuous slo			6 Wi	re wrapped		9 Drilled hol	es	, ,	
	uvered shut		y punched	7 To	rch cut	•	10 Other (spe	ecify)		
		ED INTERVALS:	From		25	ft Fron	` .	• /	0	
OOHLLIN		ED INTERNACO.	From	.					D	
(SDAVEL DA	CK INTERVALS:	From	12 # 10	25	ft Fron			0	
`	JIIAVEE FA	OK INTERVALO.	From	ft. to	-	ft., Fron		ft. to		
6 GROUT	T MATERIA	L: 1 Neat ce		2 Cement grout	3 Bento					
_	_	$\boldsymbol{\rho}$	17						ft. to	
Grout Inte				f ft., From	ft.					
		ource of possible of		7 Dit asia.		10 Livest	•		bandoned water well	
1 Septic tank 4 Lateral line							11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool				8 Sewage lagoon			12 Fertilizer storage 16 Other (specify below)			
	•	ver lines 6 Seepa	ige pit	9 Feedyard			icide storage	. 10.7.7.3.		
Direction f		1			1 50014	How man	ny feet?	DILICONO	UTEDI/ALO	
FROM	TO	A. V 12	LITHOLOGIC		FROM	ТО		PLUGGING IN	VIERVALS	
` 0	4	MARL DI	rown p	ondy yay						
4	27	prown	Sand							
				1						
		casing 1	reight	? growt	variano	25				
		1	J							
		mantea								
		<i>y</i>								
	J							0) -1,		
			S CERTIFICA	TION: This water wel	was (1) constru				ler my jurisdiction and wa	
	on (mo/day		וביות					A	wledge and belief. Kansa	
Water Wel	I Contractor	's License No	1 717	a 1/ 4 /	Well Record wa		<i>(L</i>)	AMI	Ba. O	
		me of Ground		Tech, suc		by (signat	7	my mitori	ATTON COT	
INSTRU	JCTIONS: Use to the and Environment	ypewriter or ball point penent, Bureau of Water P	n. PLEASE PRESS rotection, Topeka,	S FIRMLY and <u>PRINT</u> clearly Kansas 66620-7320. Telepho	. Please fill in blanks, ne: 913-296-5514. Se	underline or circle nd one to WATER	the correct answer	Send top three cond retain one for yo	opieto Vinus opaminad Cur records.	