			WELL RECORD	Form WWC-5		1	110	- 6
LOCATION OF WA		Fraction		I	tion Number	Township N		Range Number
County: Sedy	Wick	SE 1/4	SE 14 S	1/4	8	T 27	S	R / (E/)V
Distance and director					,			
1300	Market	3/,	Wickil	arks				
WATER WELL OV RR#, St. Address, Bo	VNER: Hmoco	Endin	Creek Par	KWay		_		
RR#, St. Address, Bo	x#:8700 7			,,,,,	<i></i>	Board of A	-	Division of Water Resources
City, State, ZIP Code	: Over	land P	ark, KS		16210	Applicatio	n Number:	
LOCATE WELL'S I								
AN "X" IN SECTIO	N IDE							
ī !	l v	ELL'S STATIC V	ATER LEVEL	<i>!.</i> ₩ ft. b	elow land sur	face measured or	n mo/day/yr	6/29/9/
	1 1/2	Pump t	est data: Well wa	ter was	ft. a	fter	. hours pu	mping gpm
NW	Es	st. Yield	gpm: Well wa	ter was	ft. a	fter	. hours pu	mping gpm
	Bo	ore Hole Diamete	r <i>G. 1</i> .4in. to	› ٦ ٠٠٠٠	ft., ;	and	in.	to
* w	ı w	ELL WATER TO	BE USED AS:	5 Public water		8 Air conditioning		Injection well
- I !		1 Domestic	3 Feedlot					Other (Specify below)
sw	36	2 Irrigation	4 Industrial	7 Lawn and	garden only 🖔	10 Monitoring we	₽,	
1 1 1	W W	as a chemical/ba	cteriological sample	submitted to D	epartment? Ye	es(No7	; If yes,	mo/day/yr sample was sub-
1	§ mi	itted			Wa	ter Well Disinfect	ed? Yes	No
TYPE OF BLANK	CASING USED:	:	Wrought iron	8 Concr	ete tile	CASING JO	INTS: Glued	Clamped
1 Steel	3 RMP (SR)	(Asbestos-Cement	9 Other	(specify below	v)	Weld	ed
2 PVC	4 ABS		⁷ Fiberglass				Threa	ided.
Blank casing diamete	r 2 in.	to	ft., Dia	in. to	·	ft., Dia		in. to ft.
Casing height above	land surface	<i>O</i> ir	., weight		Ibs./	ft. Wall thickness	or gauge N	5ch-40
TYPE OF SCREEN C				7 PV			bestos-ceme	
1 Steel	3 Stainless st	teel :	Fiberglass	8 RN	IP (SR)	11 Ot	ner (specify)	
2 Brass	4 Galvanized	steel	Concrete tile	9 AB	s	12 N o	ne used (op	en hole)
SCREEN OR PERFO	RATION OPENINGS	ARE:	5 Gau	zed wrapped		8 Saw cut		11 None (open hole)
1 Continuous sl	ot 3 Mill s	slot	6 Wire	wrapped		9 Drilled holes		
2 Louvered shu	tter 4 Key	punched	7 Toro	h cut		10 Other (specif	fy)	
SCREEN-PERFORAT	ED INTERVALS:	From	∜ ft. to .	9	ft., Froi	m	ft. t	o
								o
GRAVEL PA	ACK INTERVALS:	From	ft. to .	7	ft., From	m	ft. t	o
		From	ft. to		ft., Fro			o ft.
6 GROUT MATERIA	L: 1 Neat cem	nent (2	Cement grout,	3 Bento	onite) 4	Other		
	om ft.	to 3	ft., From	. 🚅 ft.	to	ft., From .	.	ft. to
What is the nearest s	ource of possible cor	ntamination:			10 Lives	tock pens	14 A	bandoned water well
1 Septic tank	4 Lateral I	lines	7 Pit privy		11 Fuel	storage	15 O	il well/Gas well
2 Sewer lines	5 Cess po	ool	8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)			ther (specify below)
3 Watertight ser	wer lines 6 Seepage	e pit	9 Feedyard		13 Insec	ticide storage		
Direction from well?					How ma	ny feet?		
FROM TO		LITHOLOGIC LO		FROM	то	Р	LUGGING I	NTERVALS
0 6	LTBIN	Claye	y Silt					
6 8.5	LT Bin	Clay						
		,						
8.5 13,5	OK Bin	Claves	Silt					
13,5 25	LT Gra	v Same	/					
		/						
	1							los mu jusiadiatias and
7 CONTRACTOR'S	OR LANDOWNER'S	CERTIFICATIO						der my jurisdiction and was
completed on (mo/day	y/year)	6/17					100	owledge and belief. Kansas
Water Well Contracto	r's License No	. 2 l . T	This Water				1.4.1.2.8	h
under the business n					by (signa		m)	· Sandly
INSTRUCTIONS: Use	typewriter or ball point pen ment, Bureau of Water, Top	PLEASE PRESS FIF	MLY and PRINT clearly.	Please fill in blanks,	water well of	the correct answers.	Sport top three i	copies to Kansas Department
of Health and Environ	ment, Bureau of Water, Tol	peka, Nansas 66620-7	320. Telephone: 913-296	- Jungo. Jeniu One 10	WELL U	THE THE REPORT OF	ioi your records	