


1] LOCATION OF WATER WELL: Fraction NE 1/4 SE 1/4 NW 1/4 Section Number 9 Township Number T 27 S Range Number R 1 **EW**
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city?

1927 N. Mosley Wichita Kansas

2] WATER WELL OWNER: DAVE Chipaux
 RR#, St. Address, Box # : 1927 N. Mosley Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Wichita, KS. 67214 Application Number:

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4] DEPTH OF COMPLETED WELL 35.0' ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 16.0' ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 16.5 ft. below land surface measured on mo/day/yr 9/29/89

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm Well water was ft. after hours pumping gpm

Bore Hole Diameter 6.5 in. to 35.0 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5] TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

☒ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter 2.0 in. to 15.0 ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface 0.0 in., weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: ☒ PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot ☒ Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 15.0 ft. to 35.0 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 13.0 ft. to 35.0 ft., From ft. to ft.

6] GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ Bentonite 4 Other

Grout Intervals: From 0 ft. to 13.0 ft., From ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Industry

Direction from well? North How many feet? 20.0'

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 6.5 lean clay medium blue 0 6.5

6.5 8.5 sandy lean clay light gray blue 6.5 8.5

8.5 10.0 silty sand lt. gray blue 8.5 10.0

10.0 35.0 poorly sorted coarse sand 10.0 35.0

35.0 35.0 slate 35.0 35.0

RECEIVED

NOV 09 1989

DIVISION OF ENVIRONMENT

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

completed on (mo/day/year) 9/29/89 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 471 This Water Well Record was completed on (mo/day/yr) 9/29/89

under the business name of HWS TECHNOLOGIES by (signature) [Signature]