

1 LOCATION OF WATER WELL: County: <u>Sedawick</u>		Fraction <u>NW 1/4 SW 1/4 NW 1/4</u>	Section Number <u>9</u>	Township Number <u>T 27 S</u>	Range Number <u>R 10 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>14th & Broadway, Wichita, KS</u> MW-3					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		<u>W. A. Michaplis, Jr.</u> <u>211 N. Broadway</u> <u>Wichita, KS 67201</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>24</u> ft. ELEVATION: <u>18</u> ft.			
		Depth(s) Groundwater Encountered <u>18</u> ft. 2. <u>18</u> ft. 3. <u>18</u> ft. WELL'S STATIC WATER LEVEL <u>18</u> ft. below land surface measured on mo/day/yr <u>4/8/89</u> Pump test data: Well water was <u>18</u> ft. after <u>18</u> hours pumping <u>18</u> gpm Est. Yield <u>18</u> gpm Well water was <u>18</u> ft. after <u>18</u> hours pumping <u>18</u> gpm Bore Hole Diameter <u>8</u> in. to <u>24</u> ft., and <u>8</u> in. to <u>24</u> ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No <u>X</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded <u>X</u> 7 Fiberglass Threaded <u>X</u>		Blank casing diameter <u>0.14</u> in. to <u>0.14</u> ft., Dia. <u>0.7</u> in. to <u>0.7</u> ft., Dia. <u>0.154</u> in. to <u>0.154</u> ft.			
Casing height above land surface <u>0.7</u> in., weight <u>0.7</u> lbs./ft. Wall thickness or gauge No. <u>0.154</u> in.		TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)		SCREEN-PERFORATED INTERVALS: From <u>14</u> ft. to <u>24</u> ft., From <u>14</u> ft. to <u>24</u> ft., From <u>14</u> ft. to <u>24</u> ft., From <u>14</u> ft. to <u>24</u> ft.			
GRAVEL PACK INTERVALS: From <u>12</u> ft. to <u>24</u> ft., From <u>12</u> ft. to <u>24</u> ft., From <u>12</u> ft. to <u>24</u> ft., From <u>12</u> ft. to <u>24</u> ft.		6 GROUT MATERIAL:			
1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other Grout Intervals: From <u>0</u> ft. to <u>12</u> ft., From <u>12</u> ft. to <u>12</u> ft., From <u>12</u> ft. to <u>12</u> ft., From <u>12</u> ft. to <u>12</u> ft.		What is the nearest source of possible contamination:			
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) <u>N.A.</u> 13 Insecticide storage		Direction from well? <u>How many feet?</u>			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 4 Brown SILTY CLAY					
4 8 Brown clayey SILT					
8 12 Brown SILTY CLAY					
12 17 Brown, clayey, SAND					
17 24 Brown, saturated, fine grained SAND					
grout variance casing height variance granted.					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11-7-89</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>517</u> This Water Well Record was completed on (mo/day/yr) <u>12/7/89</u> under the business name of <u>Groundwater Tech., Inc.</u> by (signature) <u>Bangma Land</u>					