

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: SEDGWICK NE	N/E 1/4 N/E 1/4 N/E 1/4	12	T 27 S	R 1 EW

Distance and direction from nearest town or city street address of well if located within city?

2199 N. WOODLAWN

2 WATER WELL OWNER: FINA OIL & CHEMICAL CO.

RR#, St. Address, Box #: P.O. BOX 2159

Board of Agriculture, Division of Water Resources

City, State, ZIP Code: DALLAS TX. 75221

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION:

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 999 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 7 1/4 in. to ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only X 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

- 1 Steel
2 PVC X
3 RMP (SR)
4 ABS

- 5 Wrought iron
6 Asbestos-Cement
7 Fiberglass
8 Concrete tile
9 Other (specify below)

- CASING JOINTS: Glued Clamped
Welded
Threaded X

Blank casing diameter 2 in. to 20 ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface in. weight sched 40 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

- 1 Steel
2 Brass
3 Stainless steel
4 Galvanized steel

- 5 Fiberglass
6 Concrete tile

- X 7 PVC
8 RMP (SR)
9 ABS
10 Asbestos-cement
11 Other (specify)
12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

- 1 Continuous slot
2 Louvered shutter
3 Mill slot X
4 Key punched

- 5 Gauzed wrapped
6 Wire wrapped
7 Torch cut
8 Saw cut
9 Drilled holes
11 None (open hole)
10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 30 ft. to 20 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 30 ft. to 18 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: X 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 17 ft. to 0.6 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

- 1 Septic tank
2 Sewer lines
3 Watertight sewer lines
4 Lateral lines
5 Cess pool
6 Seepage pit
7 Pit privy
8 Sewage lagoon
9 Feedyard

- 10 Livestock pens
X 11 Fuel storage
12 Fertilizer storage
13 Insecticide storage
14 Abandoned water well
15 Oil well/Gas well
16 Other (specify below)

Direction from well? South

How many feet? 40

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2.0	topsoil			
2.0	5.0	brn / clay			
5.0	10.0	very stiff clay turning to olive green shale @ 6.0			
10.0	21.0	same as above with tan color at 20.0			
21.0	30.0	tan shale with interbedded calcium carbonate & gypsum saturated @ 26.0			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-21-94 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 5-5-94

under the business name of Kurtz Environmental Service by (signature)