

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SE 1/4 SE 1/4 SE 1/4	15	T 27 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 3020 East Central, Wichita, Kansas					
2 WATER WELL OWNER:		Dorris Reibenspies			
RR#, St. Address, Box # :		1450 N Clarence #204		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code :		Wichita KS 67203		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 33.0' ft. ELEVATION: 1325			
		Depth(s) Groundwater Encountered 1. None ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 30.09' ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8" in. to ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile Welded			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Threaded Flush			
7 Fiberglass					
Blank casing diameter 2" in. to ft., Dia		in. to ft., Dia			
Casing height above land surface Flush in., weight 703 lbs./ft. Wall thickness or gauge No. 154					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 12.5' ft. to 32.5' ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 10.5' ft. to 32.5' ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 10.5' ft. to 1.0' ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? Southeast		How many feet? 400'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0'	4.0'	Lean clay; fill.			
4.0'	16.0'	Fat clay; Alluvium.			
16.0'	33.0'	Lean clay.			
Waiver for Flushmount Granted 4-21-92 for D & R Properties by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-22-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 5-1-92 under the business name of Geotechnical Services, Inc. by (signature) Allison Irwin					