USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

	П						
T	R	EW	sec	1/4	1/4	1/4	No.

Kansas State Dept. Of Health (Water Well Contractors) Forbes–Bldg. 740 Topeka, Kansas 66620

County	Township name	Fraction SE		Section	on number	Town number Range number				
1 Location of well: Sedgwick	WichiTA	SW SE	" "		15	7275 RIE				
Distance and direction from learest town or city: 3 Owner of well: Hemco Plbg, & HTg, I'nc,										
Street address of well location if in city: 2430 E Central 47214 Address: 11398, ST. Fe Wichita KS 67211										
Locate with "X" in section below:	Sketch map:	41211			<i>- </i>	4 Well denth: 34 ft Date of completion 3-30-76				
N	05 11.	The	>			Well diameter Z in Bore hole				
i i i	SE 1/4 of					5 Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary				
W! E	SW 1/4 of	the	•			Use: Domestic Public supply Industry				
	SE 14					☐ Irrigation ☑ Air conditioning ☐ Commercial ☐ Test well ☐				
						7 Casing: Material PVC Height: above/below				
S .						Threaded				
→1 Mile →				· · · · · · · · · · · · · · · · · · ·		in. to 23 ft. depth Drive shoe? Yes No				
2 Тур	e and color of material			From	То	9 C				
Clay Black					3	Manufacturer Clayton Mark Type Well Polat Dial 14 64.				
Clares Car La 1st	Reddist	•	م داوه د	3	7	Slot gauze LO Length 4 FT				
Clay-SAND YMIX	_	7 DIA	WH	<i>></i>	107	Set between 20 ft. and 34 ft				
Fine SANd	Light	14)1		7	17	Gravel pack Yes No Size range of material				
medium Course	gravel	DAKK BI	0101	17	23	9 Static water level: 3 ft. below land surfoce Date 3-30-746				
	water	level	_	23		10 Pumping level below land surfaces:				
mater-in unl	Kaning Sa J	-1-0322		23	34	ft. afterhrs. pumping g.p.m. ft. ofterhrs. pumping g.p.m.				
l	· •	10.7				Estimated maximum yield 20 g.p.m.				
Driven we		1				11 Water sample submitted: Yes No Date				
Top 23 ft		2			<u> </u>	12 Well head completion: SANTAR WOLLSEN				
Sunflower P.V.C.	CASING E	Concre	te			13 Well grouted? Yes No				
with SANITARY	Well Sex	1/.				Neat cement Bentonite Depth: From ft.				
						14 Nearest source of possible contamination: CI				
						ft Direction TypSelver Well disinfected upon completion? Yes No				
						15 Pump: Not installed				
					<u> </u>	Manufacturer's name HP Volts				
					ļ	Length of drop pipe ft. capacity g.m.p.				
						Type: Submersible Turbine				
(use	e a second sheet if needed)					☐ Jet ☐ Reciprocating ☐ Certrifugal ☐ Other				
		· i .	SA	11/17	TY	17 Water well contractor's certification:				
ולועק ווש דעונים	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.									
Topography: 11 3/11/erDAT	Protheroe Pumpe Well 295									
Topography: in 3 TAIL PUTE CONCRETE LAND 14 STEEL Slope						Business name License No. Address 87-74				
Upland Valley			p. *1 1	ار را	-	Signed Hall Signed Date 2007/				
Forward the white, blue and pink copies to the I	Kansas State Dept. Of Hea	Ith. J-74	ell P	TAI		Form WWC-5				