


1 LOCATION OF WATER WELL: County: Salgarick Fraction: NE SE NW NE 1/4 Section Number: 16 Township Number: T 27 S Range Number: R 1 E

Distance and direction from nearest town or city street address of well if located within city? 1245 n River Blv.

2 WATER WELL OWNER: Mr Stucky Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 1245 n River Blv. Application Number: none
City, State, ZIP Code: Wichita Kansas 67203

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: 1300

Depth(s) Groundwater Encountered 1. 17 ft. 2. 17 ft. 3. 17 ft.

WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 5-1-94

Pump test data: Well water was 17 ft. after 5-1-94 hours pumping 5-1-94 gpm

Est. Yield 17 gpm: Well water was 17 ft. after 5-1-94 hours pumping 5-1-94 gpm

Bore Hole Diameter 17 in. to 17 ft., and 17 in. to 17 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 1 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X
2 PVC 4 ABS 7 Fiberglass Threaded X

Blank casing diameter 5 in. to 5 ft., Dia. 5 in. to 5 ft., Dia. 5 in. to 5 ft.

Casing height above land surface 36 in., weight 36 lbs./ft. Wall thickness or gauge No. 36

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 3 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) NA

SCREEN-PERFORATED INTERVALS: From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft.

GRAVEL PACK INTERVALS: From NA ft. to NA ft., From NA ft. to NA ft., From NA ft. to NA ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 17 ft. to 3 ft., From 17 ft. to 3 ft., From 17 ft. to 3 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) NONE
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
35	17	<u>Sand Filler</u> <u>Cement Grout</u> <u>Top Soil</u>			
17	3				
3	0				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-29-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 472 This Water Well Record was completed on (mo/day/yr) 5-1-94 under the business name of Beards Pump & Well Serv by (signature) David R Beck