

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	NW 1/4 NE 1/4 SW 1/4	16	T 27 S	R 1 E

Distance and direction from nearest town or city street address of well if located within city?

918 N Santa Fe Wichita Ks**WNO-428**

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : City of Wichita 1900 E 9th	Application Number:
City, State, ZIP Code : Wichita Ks	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 13 ft. 2. 13 ft. 3. 13 ft.
	WELL'S STATIC WATER LEVEL 13 ft. below land surface measured on mo/day/yr
	Pump test data: Well water was 13 ft. after 13 hours pumping 13 gpm
	Est. Yield 13 gpm: Well water was 13 ft. after 13 hours pumping 13 gpm
	Bore Hole Diameter 13 in. to 13 ft., and 13 in. to 13 ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)
	Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped X
1 Steel	3 RMP (SR)	9 Other (specify below)	Welded X
2 PVC	4 ABS		Threaded X
Blank casing diameter 2 in. to 10 ft., Dia 10 in. to 10 ft., Dia 10 in. to 10 ft.	7 Fiberglass		
Casing height above land surface 10 in., weight 10 lbs./ft. Wall thickness or gauge No. 10			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 20 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 8 ft., From 8 ft. to 8 ft., From 8 ft. to 8 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: 3 From 8 ft. to 7 ft. 2 From 7 ft. to 0 ft., From 0 ft. to 0 ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage	Groundwater		
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well?	How many feet? 0			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Asphalt			
0.5	3	Fill material			
3	4	Clay Dark Brown			
4	6	Silty Clay			
6	8	Silty Sand			
8	10.5	Silty Sandy Clay			
10.5	14	Silty Clay			
14	20	SAND Med-Coarse with Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/26/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 4/3/93 under the business name of Groundwater Technology by (signature) Dennis White
