

1 LOCATION OF WATER WELL: County: SEDGWICK Fraction: NW 1/4 NE 1/4 NW 1/4 Section Number: 16 Township Number: 27 S Range Number: 1 EW Distance and direction from nearest town or city street address of well if located within city? 10th & Santa Fe, NW corner, Wichita, KS; 22' W of Santa Fe, 25' north of 10th

2 WATER WELL OWNER: Associated Property Service RR#, St. Address, Box #: 818 W. Emporia, Suite 100 City, State, ZIP Code: Wichita, KS 67214 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NW section of the top-left 4-section block]

4 DEPTH OF COMPLETED WELL: ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 in. to BOTTOM ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter: 2 in. to ft. Dia. in. to ft. Dia. in. to ft. Dia. in. to ft. Blank casing height above land surface: 0 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 4 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 24 ft. to 14 ft. From 11 ft. to 12 ft. GRAVEL PACK INTERVALS: From 24 ft. to 12 ft. From 11 ft. to 12 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Vol-CRAY Grout Intervals: From 11 ft. to 12 ft. From 11 ft. to 12 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage How many feet?

DIRECTION FROM WELL? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0	3	Dry, black friable, silty sand		
3	4	Hard, dk br, slightly plastic, sandy clay		
4	9	Med br, hard, slightly plastic, sandy clay		
9	10	Med br, Very fine sand		
10	14	Med br, med-coarse gr. sand		
14	19	Med br, coarse sand, clay near bottom		
19	24	Med br, med. sat. coarse sand		

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-22-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 524 This Water Well Record was completed on (mo/day/yr) 10-11-90 under the business name of ALLIED LAB by (signature) Richard J. Allen

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-298-5545. Send one to WATER WELL OWNER and retain one for your records.