1 LOCATION OF WATER WELL:	FRACTION	Water Well Recor	d Form WWC-5			T
Sedgwick		200.0		Section Number	Township Number	Range Number
	NE 1/4		NW 1/4	18	T 27 s	R 1E EW
Distance and direction frem nearest town or city street address of well if located within city? 1355 Iroquois Wichita, Kansas						
1355 Iroquois Wichita, Kansas 2 WATER WELL OWNER: NELSON, Bill						
	5 Iroquois				Board of Agriculture, D	ivivsion of Water Resource
1 200	hita, Kansas				Application Number:	
3 LOCATE WELL'S LOCATION WITH	4 DEPTH OF COM		40	ft, ELE	EVATION:	[•
AN "X" IN SECTION BOX:	Depth(s) groundwa		1	ft.	2 ft.	3 ft.
	WELL'S STATIC W				RFACE MEASURED ON mo/day/yr	07/31/1993
	Pump test		water was		after hours pum	
NW NE	Est. Yieid		water was		after hours pum	
E W	Bore Hole Diameter	12 in.	to 40	ft.,	and in.	to ft.
= "	WELL WATER TO B	BE USED AS:	5 Public water	r supply	8 Air conditioning 11 Is	njection well
STE	1 Domestic	3 Feedlot	6 Oil field wa	ter supply	9 Dewatering 12 C	Other (Specify below)
	2 Irrigation	4 Industrial	7 Lawn and g	arden only 1	0 Monitoring well	
	Was a chemical/bacte	riological sample st	ıbmitted to De	partment? Yes	No 🗶 ; If yes, m	o/day/yr sample was
S	submitted			Wat	ter Well Disinfected? Yes	X No
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped						
1 Steel 3 RMP (SR)		6 Asbestos-Ceme	nt 9	Other (Specify be	elow) W	/elded
2 PVC 4 ABS		7 Flberglass	S	DR-26	T	hreaded
Blank casing Diameter 5	in. to 24	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height above land surface		weight 2			Wall thickness or gauge No.	.214
TYPE OF SCREEN OR PERFORA	TION MATERIAL:	5 Fiberglass		PVC DMD (SD)	10 Asbestos-ceme	
1 Steel 3 Stainless Steel	•	6 Concrete tile		RMP (SR)	11 other (specify	
2 Brass 4 Galvanized stee		o Concrete the	9	ABS	12 None used (op	·
SCREEN OR PERFORATION OPENING ARE:			5 Gauzed wrapped		8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes						
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATION INTERV	VALS: from 24	ft.	to 40	ft., From	ft. to	ft.
	from		. to	ft., From		ft.
GRAVEL PACK INTER			. to 40	ft., From		ft.
6 GROUT MATERIAL: 1 Neat	from cement 2 C	ement grout	. to	ft., From tonite	4 Other	ft.
Grout Intervals: From 4	ft. to 24					
What is the nearest source of possible		ft., From	ft. 1	to 10 Livesto	ft., From ck pens 14 A	ft. to ft. bandon water well
1 Septic tank 4 Lateral lines		7 Pit privy				oil well/Gas well
2 Sewer lines 5 Cess pool					tilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage						
Direction from well? Southwest How many feet? 50						
FROM TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTER	RVALS
0 2 sandy to	p soil	=1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-				
2 40 medium t	o coarse sa	and				
		~~~~~~				
				1		
				1		
	, ,			ļ		
					**************************************	
			<u> </u>			
7 CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATION: This	s water well was (	1) <u>constructe</u>	d, (2) reconstru	icted, or (3) plugged under m	y jurisdiction and
was completed on (mo/day/year)						
Under the business name of H	arp Well &	inis water Well R Pump	ecord was co	mo hy voices		
Under the business name of Harp Well & Pump by (signature) fane Frederick						
665					<i>x</i>	