

1 LOCATION OF WATER WELL:		Fraction SW	Section Number 19	Township Number 27 S	Range Number 1 E
County: Sedgwick SE		Distance and direction from nearest town or city street address of well if located within city? 147 S. Athenian			
2 WATER WELL OWNER: Liles, John R					
RR#, St. Address, Box #: 147 S. Athenian					
City, State, ZIP Code: Wichita KS 67213					
Board of Agriculture, Division of Water Resources Application Number: NA					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 29 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 18 ft. 2. 18 ft. 3. 18 ft.			
		WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was 20 ft. after 1 hours pumping 10 gpm			
		Est. Yield 30 gpm: Well water was 20 ft. after 1 hours pumping 10 gpm			
		Bore Hole Diameter 7 in. to 15 in. and 1 1/4 in. to 29 in.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)					
Blank casing diameter 4 in. to 15 in. Dia 1 1/4 in. to 29 in. Dia 29 in. to 29 in.					
Casing height above land surface 12 in. weight 1 lbs./ft. Wall thickness or gauge No. SDR 26					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)					
SCREEN-PERFORATED INTERVALS: From 25 ft. to 29 ft. From 25 ft. to 29 ft. From 25 ft. to 29 ft. From 25 ft. to 29 ft.					
GRAVEL PACK INTERVALS: From 25 ft. to 29 ft. From 25 ft. to 29 ft. From 25 ft. to 29 ft. From 25 ft. to 29 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 14 ft. From 0 ft. to 14 ft. From 0 ft. to 14 ft. From 0 ft. to 14 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)					
Direction from well? North How many feet? 10					
LITHOLOGIC LOG					
FROM	TO	LITHOLOGIC LOG			
0	6	Drk Brn Clay			
6	8	LT Brn sand/clay loam			
8	15	LT Brn fine sand			
15	29	unknown SAND point driven well			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-6-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 295 This Water Well Record was completed on (mo/day/year) 4-6-85 under the business name of Protheroe Pump & Well by (signature) Glenn Protheroe					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4