

1 LOCATION OF WATER WELL: County: <u>Sedgewick</u>		Fraction <u>NW 1/4 SE 1/4 NW 1/4</u>	Section Number <u>21</u>	Township Number T <u>27</u> S	Range Number R <u>1</u> <u>EN</u>
Distance and direction from nearest town or city street address of well if located within city? <u>NW of 1st & Moore Street, Wichita KS Factory "B" RW-5</u>					
2 WATER WELL OWNER: RR#, St. Address, Box # : <u>The Coleman Company</u> <u>250 N. St. Francis</u> City, State, ZIP Code : <u>Wichita, KS 67202</u>				Board of Agriculture, Division of Water Resources Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>30</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>13.5</u> ft. 2. <u>13.6</u> ft. 3. <u>10/11/93</u> WELL'S STATIC WATER LEVEL <u>13.6</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>11.25</u> ft. after <u>31</u> hours pumping <u>10/11/93</u> gpm Est. Yield <u>11.25</u> gpm: Well water was <u>31</u> ft. after <u>10/11/93</u> hours pumping <u>11.25</u> gpm Bore Hole Diameter <u>11.25</u> in. to <u>31</u> ft., and <u>31</u> in. to <u>31</u> ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued.....Clamped..... <u>7 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded..... Blank casing diameter <u>5</u> in. to <u>15</u> ft., Dia. <u>15</u> in. to <u>15</u> ft., Dia. <u>15</u> in. to <u>15</u> ft. Casing height above land surface <u>3.6</u> in., weight <u>3.6</u> lbs./ft. Wall thickness or gauge No. <u>SEL 40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: <u>7 PVC</u> 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)..... 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot <u>3 Mill slot</u> 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)..... SCREEN-PERFORATED INTERVALS: From <u>15</u> ft. to <u>30</u> ft., From <u>15</u> ft. to <u>30</u> ft., From <u>15</u> ft. to <u>30</u> ft. GRAVEL PACK INTERVALS: From <u>13</u> ft. to <u>30</u> ft., From <u>13</u> ft. to <u>30</u> ft., From <u>13</u> ft. to <u>30</u> ft.					
6 GROUT MATERIAL: <u>1 Neat cement</u> 2 Cement grout <u>3 Bentonite</u> 4 Other..... Grout Intervals: From <u>11</u> ft. to <u>surface</u> ft., From <u>13</u> ft. to <u>11</u> ft., From <u>13</u> ft. to <u>11</u> ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS <u>0</u> <u>13</u> <u>Clay</u> <u>13</u> <u>11</u> <u>Variance Applied for</u> <u>13</u> <u>30</u> <u>SAND med</u> <u>30</u> <u>31</u> <u>CLAY</u>					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-11-93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>517</u> This Water Well Record was completed on (mo/day/yr) <u>11-10-93</u> under the business name of <u>Groundwater Technology Inc</u> by (signature) <u>Albert Stout</u>					