

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number		
County: Sedgwick		NE 1/4 NW 1/4 NW 1/4		21		T 27 S		R 1 EW		
Distance and direction from nearest town or city street address of well if located within city?										
Beneath Address 601 E. Central										
2 WATER WELL OWNER: Mr. Jack Shively					Board of Agriculture, Division of Water Resources					
RR#, St. Address, Box #: 601 E Central					Application Number:					
City, State, ZIP Code: Wichita Kansas 67202										
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 25.0 ft. ELEVATION: N/A							
			Depth(s) Groundwater Encountered 1. 15.0 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 15.84 ft. below land surface measured on mo/day/yr 1/4/90 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 4.0 in. to 25.0 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED:										
1 Steel			3 RMP (SR)		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued Clamped	
2 PVC			4 ABS		6 Asbestos-Cement		9 Other (specify below)		Welded	
					7 Fiberglass				Threaded X	
Blank casing diameter 2.0 in. to 15.0 ft. Dia in. to ft. Dia in. to ft.										
Casing height above land surface Flush in. weight lbs./ft. Wall thickness or gauge No. Sch. 40										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1 Steel			3 Stainless steel		5 Fiberglass		8 RMP (SR)		10 Asbestos-cement	
2 Brass			4 Galvanized steel		6 Concrete tile		9 ABS		11 Other (specify)	
SCREEN OR PERFORATION OPENINGS ARE:										
1 Continuous slot			2 Mill slot		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
2 Louvered shutter			4 Key punched		6 Wire wrapped		9 Drilled holes			
SCREEN-PERFORATED INTERVALS:										
From 15.0 ft. to 25.0 ft.			From 15.0 ft. to 25.0 ft.			From 15.0-25.0 ft. to Natural				
GRAVEL PACK INTERVALS:										
From 13.0 ft. to 15.0 ft.			From 15.0 ft. to 15.0-25.0 ft.			From 15.0-25.0 ft. to Natural				
6 GROUT MATERIAL:										
1 Neat cement			2 Cement grout		3 Bentonite		4 Other			
Grout Intervals: From Grade ft. to 10.0 ft. From ft. to ft. From ft. to ft.										
What is the nearest source of possible contamination:										
1 Septic tank			4 Lateral lines		7 Pit privy		10 Livestock pens		14 Abandoned water well	
2 Sewer lines			5 Cess pool		8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well	
3 Watertight sewer lines			6 Seepage pit		9 Feedyard		12 Fertilizer storage		16 Other (specify below)	
Direction from well? North-East										
How many feet? 10.0										
LITHOLOGIC LOG										
FROM	TO									
0	6"	Concrete								
6"	2.0'	Silty Clay: dark brown; with sand								
2.0	4.5	Silty Clay: light brown; with sand								
4.5	5.0	Silty sand: light brown; fine with silt								
5.0	15.0	Sand: light brown with fine sand								
15.0	25.0	Gravelly Sand: grayish-brown; 3-5% gravel; with coarse sand								
PLUGGING INTERVALS										
FROM	TO									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/3/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 471 This Water Well Record was completed on (mo/day/yr) 1/10/90 under the business name of HWS Technologies Inc. by (signature) Richard L. Starnes										