

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NE 1/4 SE 1/4 NW 1/4	Section Number 21	Township Number T 27 S	Range Number R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 399.0 ft. South of the Mead and Douglas Intersection					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		The Coleman Company 250 North St. Francis Wichita, Kansas 67202			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 36.0 ft. ELEVATION: n/a Depth(s) Groundwater Encountered 1. 14.0 ft. 2. _____ ft. 3. _____ ft. WELL'S STATIC WATER LEVEL 14.0 ft. below land surface measured on mo/day/yr 02/21/90 Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm Est. Yield _____ gpm Well water was _____ ft. after _____ hours pumping _____ gpm Bore Hole Diameter 6.5 in. to 36.0 ft. and _____ in. to _____ ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes _____ No X ; If yes, mo/day/yr sample was sub- mitted _____ Water Well Disinfected? Yes _____ No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 2.0 in. to 10.0 ft. Dia 2.0 in. to 26.0 ft. Dia _____ in. to _____ ft. Casing height above land surface flush in. weight _____ lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) _____ SCREEN-PERFORATED INTERVALS: From 10.0 ft. to 20.0 ft. From _____ ft. to _____ ft. From 26.0 ft. to 36.0 ft. From _____ ft. to _____ ft. GRAVEL PACK INTERVALS: From 8.0 ft. to 36.0 ft. From _____ ft. to _____ ft. From _____ ft. to _____ ft. From _____ ft. to _____ ft.		CASING JOINTS: Glued _____ Clamped _____ Welded _____ Threaded X 6 Asbestos-Cement 9 Other (specify below) _____ 7 Fiberglass _____ 10 Asbestos-cement _____ 11 Other (specify) _____ 12 None used (open hole) _____			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Volclay Grout		Grout Intervals: From 0.0 ft. to 8.0 ft. From _____ ft. to _____ ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) _____ 13 Insecticide storage _____ Direction from well? Northeast How many feet? 40.0			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0.0	0.5	Concrete			
0.5	3.0	Silty Lean Clay; mottled light and dark brown.			
3.0	5.0	Sandy Silt; light brown.			
5.0	7.0	Silty Fat Clay; mottled light gray and light brown.			
7.0	8.0	Sandy Silt; mottled light gray and light brown.			
8.0	11.0	Poorly sorted very fine sand.			
11.0	14.0	Well sorted fine sand; stained black.			
14.0	20.0	Poorly sorted fine sand; stained black.			
20.0	36.0	Well sorted coarse sand.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/16/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 471 This Water Well Record was completed on (mo/day/yr) 2/22/90 under the business name of HWS Technologies Inc. by (signature) <i>[Signature]</i>					