

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NW 1/4 SE 1/4 NW 1/4	21	T 27 S	R 1
Distance and direction from nearest town or city street address of well if located within city? Southwest corner of the intersection of 1st St. and Sante Fe <div style="text-align: right;">EAST</div>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 35.0 ft. ELEVATION: 1298.0			
		Depth(s) Groundwater Encountered 1. 16.0 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 16.0 ft. below land surface measured on mo/day/yr 6/5/89			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 6.5 in. to 35.0 ft., and in. to ft.			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded			
Blank casing diameter 2.0 in. to 13.0 ft., Dia 2.0 in. to 25.0 ft., Dia in. to ft.					
Casing height above land surface 0.0 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 13.0 ft. to 23.0 ft., From 25.0 ft. to 35.0 ft.					
GRAVEL PACK INTERVALS: From 11.33 ft. to 23.0 ft., From 20.0 ft. to 35.0 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Volclay Grout					
Grout Intervals: From 0.5 ft. to 11.33 ft., From 5 ft. to 20.0 ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Industry					
Direction from well? Northwest		How many feet? 200			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5.0	Silty clay mot. lt. brn. v. dk. brn.			
5.0	7.0	Poorly sorted v. fine sand lt. brown			
7.0	15.5	Well sorted fine sand light brown			
15.5	17.5	Well sorted coarse sand red brown			
17.5	27.0	Well sorted coarse sand drk. tan			
27.0	35.0	Well sorted coarse sand drk. tan			
35.0	36.0	Shale lt. gray and drk. gray			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (x) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/5/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 471 This Water Well Record was completed on (mo/day/yr) 6/9/89 under the business name of HWS Technologies by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4