

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW 1/4 SE 1/4 NW 1/4	Section Number 21	Township Number T 27 S	Range Number R 1
Distance and direction from nearest town or city street address of well if located within city? 400' south of 250 North St. Francis					
2 WATER WELL OWNER: Coleman Group One- HCL RR#, St. Address, Box # : 250 North St. Francis City, State, ZIP Code : Wichita, KS 67214			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 36.0 ft. ELEVATION: 1263.44			
		Depth(s) Groundwater Encountered 1. 17.0 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 17.76 ft. below land surface measured on mo/day/yr 3/24/89			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 6.0 in. to 36.0 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No ☒			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped	
☒ PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
		7 Fiberglass		Threaded ☒	
Blank casing diameter 2.0 in. to 25.0 ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface Flush in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify)			
		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot ☒ Mill slot		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
2 Louvered shutter 4 Key punched		6 Wire wrapped 9 Drilled holes			
		7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 25.0 ft. to 35.0 ft. From ft. to ft.					
From 10.0 ft. to 20.0 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 8.0 ft. to 36.5 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Volclay Grout					
Grout Intervals: From 0.0 ft. to 8.0 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy		10 Livestock pens 14 Abandoned water well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon		11 Fuel storage 15 Oil well/Gas well			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		12 Fertilizer storage 16 Other (specify below)			
		13 Insecticide storage Manufacturing			
Direction from well? Northeast		How many feet? 200			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.33	Concrete			
.33	9.0	Silty sand			
9.0	13.5	Poorly sorted fine sand			
13.5	28.0	Well sorted fine sand			
28.0	31.0	Well sorted coarse sand			
31.0	32.5	Well sorted fine sand			
32.5	36.0	Well sorted coarse sand			
36.0	36.5	Weathered shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/22/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 471 This Water Well Record was completed on (mo/day/yr) 5/31/89 under the business name of HWS Technologies Inc. by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4