Form WWC-5 KSA 82a-1212

Fraction 1 LOCATION OF WATER WELL: Section Number Township Number Range Number 89E 14 NOW 1/4 Sedawick County: Distance and direction from nearest town or city street address of well if located within city? EAST 100' southwest of 250 N. St. Francis water well owner: Coleman Group One - HCL RR#, St. Address, Box # : 250 N. St. Francis Board of Agriculture, Division of Water Resources Wichita, KS 67214 City, State, ZIP Code Application Number: LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 34.0 ft. ELEVATION: 1264.68 AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1. 16.71 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 16.71. ft. below land surface measured on mo/day/yr 3/24/89...... Pump test data: Well water was ft. after hours pumping gpm NW -- NF --Est. Yield gpm: Well water was hours pumping gpm Bore Hole Diameter 6.0 ... in. to ... 36.5 ft., and in. to ft. W WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 6 Oil field water supply 12 Other (Specify below) 1 Domestic 3 Feedlot 9 Dewatering SE -7 Lawn and garden only 19 Monitoring well 2 Irrigation 4 Industrial Was a chemical/bacteriological sample submitted to Department? Yes.......No...x.....; If yes, mo/day/yr sample was sub-Water Well Disinfected? Yes TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) X PVC 4 ABS 7 Fiberglass Threaded....X....... Blank casing diameterin. toft., Diain. toft., Diaft., Diaft. TYPE OF SCREEN OR PERFORATION MATERIAL: X PVC 10 Asbestos-cement 3 Stainless steel 5 Fiberglass 8 RMP (SR) 1 Steel 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) X3 Mill slot 6 Wire wrapped 9 Drilled holes 1 Continuous slot 2 Louvered shutter 4 Key punched 7 Torch cut From 24.0 ... ft. to ... 34.0 ... ft. From ... ft. to ... ft. SCREEN-PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ft., From ft. to 4 Other Volclay. Grout 1 Neat cement 3 Bentonite 6 GROUT MATERIAL: 2 Cement grout Grout Intervals: From....0.0...ft. to...8.0.....ft., From..........ft. to...........ft., From...........ft. ft. to...........ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 7 Pit privy 1 Septic tank 4 Lateral lines 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 2 Sewer lines 5 Cess pool 8 Sewage lagoon 16 Other (specify below) ... Manufacturing 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 100.0 East Direction from well? How many feet? PLUGGING INTERVALS LITHOLOGIC LOG FROM FROM TO .33 Concrete 33 2.5 Silty clay 2.5 8.5 Silty sand 13.5 Poorly sorted fine sand 8.5 18.5 Well sorted fine sand 30.5 Well sorted coarse sand 34.0 Poorly sorted fine sand 30.5 34.0 36.5 Weathered shale 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (xt) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was and this record is true to the best of my knowledge and belief. Kansas by (signature) May

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct ans

of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.