522B		WATER	R WELL RECORD	Form WWC-5	KSA 82	a-1212		
LOCATION OF WA		Fraction	NIL!		ction Number	2'7		Range Number
County: Sedgwic		NE 1/4	NW 1/4	SE 1/4		т 27	s I	R 1 (E)W
		-	Idress of well if locate	a within city?				
	Laura Wic							
	WNER: City of							
RR#, St. Address, Bo	-,	. 9th Stre	et			•		vision of Water Resource
City, State, ZIP Code		a KS 6				Application Nu		
LOCATE WELL'S I								
AN A IN SECTIO	N 50X.	epth(s) Groundv	vater Encountered 1	14.0	ft.	2	ft. 3	
ī!	T ! W		_					
\w	NE							ping gpm
	E							ping gpm
# w i	_₽ B	ore Hole Diame	ter . <u>1 1</u> in. to		ft.,	and	in. t	o
¥ " !	X: \	ELL WATER TO	O BE USED AS:	5 Public water	er supply	8 Air conditioning	11 ln	jection well
w	SE	1 Domestic	3 Feedlot	6 Oil field wa	ter supply	9 Dewatering	12 O	ther (Specify below)
	1 7 1 1	2 Irrigation				10 Monitoring well		
<u> </u>	l W	/as a chemical/b	acteriological sample	submitted to D	epartment? \	'esNoXX	; If yes, n	no/day/yr sample was su
L	S m	itted			W	ater Well Disinfected?	Yes	No XX
TYPE OF BLANK	CASING USED:		5 Wrought iron	8 Concr	ete tile	CASING JOINTS	S: Glued .	Clamped
1 Steel	3 RMP (SR)		6 Asbestos-Cement	9 Other	(specify belo	w)	Welded	1
2 PVC	4 ABS		7 Fiberglass				Thread	ed Flush
Blank casing diamete	r 4 in	. to	ft., Dia	in. to		ft., Dia	in.	. to ft
Casing height above	and surfaceF1	นธh · · · · · · ·	in., weight 2	<u>2</u> <u></u>	Ibs.	/ft. Wall thickness or g	auge No.	25
TYPE OF SCREEN (OR PERFORATION	MATERIAL:		Z PV		10 Asbesto	s-cement	t e
1 Steel	3 Stainless s	teel	5 Fiberglass	8 RM	1P (SR)	11 Other (s	specify) .	
2 Brass	4 Galvanized	steel	6 Concrete tile	9 AB	S	12 None u	sed (oper	n hole)
SCREEN OR PERFO	RATION OPENINGS	ARE:	5 Gauz	ed wrapped		8 Saw cut	1	11 None (open hole)
1 Continuous si	ot 3 Mill	slot	6 Wire	wrapped		9 Drilled holes		
2 Louvered shu	tter 4 Key	punched	7 Torch					
SCREEN-PERFORAT	ED INTERVALS:	From 19	4 ft. to .	9 • 4	ft., Fro	m	ft. to.	
GRAVEL PA	ACK INTERVALS:	From20	.5 ft. to .	6 . 9	ft., Fro	m	ft. to.	
		From	ft. to		ft., Fro		ft. to	ft
GROUT MATERIA		_	Cement grout					
Grout Intervals: Fro	om6.9ft.	to 6.0	ft., From 6	5. . .0 ft.	to 1 • C	ft., From		ft. to
What is the nearest s	ource of possible co	ntamination:			10 Lives	stock pens	14 Aba	indoned water well
 Septic tank 	4 Lateral	lines	7 Pit privy		11 Fuel	storage	_	
2 Sewer lines	5 Cess po	ool	8 Sewage lag	oon	12 Ferti			er (specify below)
3 Watertight set	wer lines 6 Seepag	e pit	9 Feedyard		13 Inse	cticide storage S	Still.	Checking
Direction from well?						ny feet?	01110 111	
FROM TO		LITHOLOGIC L	.OG	FROM	то	PLUG	GING INT	ERVALS
0.0 0.25	1							
0.25 4.0	,	ty clay lo						
4.0 6.8		•	fine sand.					
6.8 12.8	t and the second	edium sand						
12.8 20.5	Sand. Fi	nes upward	 Very fine 		<u> </u>			
	to medium	to very	coarse.					
			.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
	4.77							
CONTRACTOR'S	OR LANDOWNER'S	CERTIFICATIO	ON: This water well w	as (1) constru	cted (2) rec	onstructed, or (3) plugo	ed under	my jurisdiction and was
								ledge and belief. Kansas
						on (mo/day/yr)		
under the business na					by (signa	/ / / / /	21	Lowen
				ease fill in blanks		e the correct answers. Send to	op three co	pies to Kansas Department
of Health and Environ	ment, Bureau of Water, To	peka, Kansas 66620	-0001. Telephone: 913-296-	5545. Send one to	WATER WELL C	WNER and retain one for you	ır records.	