

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction: NW 1/4 SE 1/4 NW 1/4	Section Number: 21	Township Number: T 27 S	Range Number: R 1 E
Distance and direction from nearest town or city street, address of well if located within city? 250 N. St Francis, Wichita, KS - FACTORY "A" RW-2					
2 WATER WELL OWNER: The Coleman Company		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 250 N. St. Francis		Application Number: 1301.39			
City, State, ZIP Code: WICHITA, KS 67202					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 36.5 ft. ELEVATION: 1301.39			
		Depth(s) Groundwater Encountered: 16.50 ft. 2. 17 ft. 3. 17 ft.			
		WELL'S STATIC WATER LEVEL: 16.50 ft. below land surface measured on mo/day/yr 2-13-92			
		Pump test data: Well water was 40 gpm. Well water was 27 gpm. Well water was 40 gpm.			
		Bore Hole Diameter: 12 in. to 36.5 ft. and 40 in. to 40 ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☐ No ☒			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued ☐ Clamped ☐			
1 Steel 3 RMP (SR) 5 Wrought iron 2 PVC 4 ABS 6 Asbestos-Cement 8 Concrete tile 7 Fiberglass 9 Other (specify below) Welded ☐ Threaded ☒					
Blank casing diameter: 6 in. to 21.5 ft. Dia		ft. Dia 18.97 in. to 1280 ft.			
Casing height above land surface: 30 in. weight 18.97 lbs./ft. Wall thickness or gauge No. 280					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:		From 21.5 ft. to 36.5 ft. From 15 ft. to 36.5 ft.			
GRAVEL PACK INTERVALS:		From 15 ft. to 36.5 ft. From 15 ft. to 13 ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite grout			
Grout Intervals: From 0 ft. to 2 ft. From 13 ft. to 15 ft. From 2 ft. to 13 ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? EAST		How many feet? 50'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	Clay			
7	32	SAND			
32	36.5	Clay			
36.5	38.5	Sand			
38.5	-	Shale			
VARIANCES APPLIED FOR					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-7-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 2/26/92 under the business name of Groundwater Technology, Inc. by (signature) Steven R. Mutch					