			WAIL	H WELL RECORD	Form vv		32a-1212				
	ON OF WAT		Fraction	~	A1/ 1	Section Numb		nip Number	Range Nu		
County: 5	edqu	rick	NW 1/4		NW1/4	2/	<u> </u>	27 s	R /	E/W	
Distance a		_		ddress of well if loo			, 0	_ ,	1		
<i>250</i>	N.	St. Fra	ncis	Wichita	KS	Fac	ctory 13	Easts	ide		
WATER	WELL OW	NER: The	Coleman	Compas	n. 17			SP-3			
,	Address, Box		V. St. F		7		Board	d of Agriculture,	Division of Water	r Resources	
-	ZIP Code	Wick	,	5 6720	ح		Appli	cation Number:			
LOCATE		CATION WITH 4	DEPTH OF C	OMPLETED WELL	30.4	ft. ELE	VATION:				
ر آ	!	1 [L		water Encountered WATER LEVEL							
		\	Pum	p test data: Well v	water was .	ft	. after	hours pu	imping	gpm	
	- NX1	\(E	st. Yield	gpm: Well v	water was .	ft	. after	hours pu	umping	gpm	
.			Bore Hole Diame	eter 8 in.	to 3	5. /	t., and	ir	n. to		
░₩┢	-i i	EI		TO BE USED AS:		water supply	8 Air conditi		Injection well		
-	i	i	1 Domestic	3 Feedlot		d water supply			Other (Specify b	nelow)	
-	- SW	SE	2 Irrigation	4 Industrial				well Air	Sparge	well	
	! !	!	•	bacteriological samp							
Į ∟				bacteriological samp	Jie Submitteu	•				שוק was sub	
- 1	S		nitted				Water Well Disir		No A	<u> </u>	
J TYPE C	OF BLANK C	ASING USED:		5 Wrought iron		concrete tile			d Clamp	ed	
1 Ste		3 RMP (SR)	1	6 Asbestos-Ceme	ent 9 C	Other (specify be	elow)	Weld	ded	, · · · · · · · · · ·	
2 PV	C	4 ABS	20	7 Fiberglass				. Thre	aded		
				.5 ft., Dia							
Casing hei	ght above la	ind surface F.	u.sh	.in., weight			os./ft. Wall thick	ness or gauge N	lo		
TYPE OF	SCREEN OF	R PERFORATION	MATERIAL:			7 PVC	10	Asbestos-cem	ent		
1 Ste		3 Stainless		5 Fiberglass		8 RMP (SR)	1.	Other (specify)		
2 Bra		4 Galvanize		6 Concrete tile		9 ABS		2 None used (or			
		RATION OPENING			auzed wrapp	ed	8 Saw cut		11 None (oper	n hole)	
					ire wrapped	_	9 Drilled h		· · · · · · · · · · · · · · · · · · ·		
	ntinuous slo				orch cut						
-	uvered shutt	-	punched 3/			5	TO Other (s	pecny)	to	٠٠٠٠٠٠٠	
SCREEN-F	PERFORATE	ED INTERVALS:	From								
				ft. t	0	ا ، ا نظر	-rom	π.	to	π.	
G	RAVEL PAG	CK INTERVALS:	From 3.	/ ft. t	o 	ft., I	From	ft.	to	ft.	
			From	ft. t			-rom	ft.		ft.	
GROUT	MATERIAL			2 Cement grout		Bentonite			bento		
Grout Inter	vals: From	n 2. 5 fi	t. to 3	ft., From		ft. to	ft., Fro	om	ft. to	ft.	
What is the	e nearest so	ource of possible c	ontamination:			10 Li	vestock pens	14 /	Abandoned water	r well	
1 Se	ptic tank	4 Lateral	lines	7 Pit privy		11 Fu	el storage	15 (Dil well/Gas well		
2 Sewer lines 5 Cess poo			ool				2 Fertilizer storage 16 Other (specify below)				
	atertight sew			_			13 Insecticide storage				
_		West	go pa	o . oouyu.	_		•	50			
Direction f	TO TO		LITHOLOGIC	LOG	FRC		inany leet:	PLUGGING	INTERVALS		
					- 1.7.0	,					
0	0,5	Conc		WP + SIL	-						
0.5	7	clayery	tine 3/7	NP F JAL							
	9	Sand	CLAY	-1-1-1							
9_	14.5	silty'	file	SAND							
14.5	30,5	med te	s fine S		tree	7	re som	-L			
30.5	21	silta	CLAY	gray Ol	re some	26m					
				/ /							
			1,00000								
							1				
							<u> </u>				
]										
CONT	PACTOR'S	OR LANDOWNER'	S CERTIFICAT	ION: This water we	l was (1) co	onstructed (2) r	econstructed, or	r (3) plugged un	der my jurisdiction	on and was	
	on (mo/day		2/- 53			and this r	ecord is true to	the best of my ki	nowledge and be	lief. Kansas	
		,,	517	Thie Wate	ar Well Beco		ed on (mo/day/	60 / //	193		
		s License No	1	Ta-/	一		~ //	2 + 00			
	business na			1 == 4.	fuc,		gnature)	ry Ole	THA		
INSTRU of Healt	CTIONS: Use ty th and Environm	pewriter or ball point pe ent, Bureau of Water, T	en. <i>PLEASE PRESS I</i> opeka, Kansas 6662	FIRMLY and PRINT clear 20-0001. Telephone: 913-	y. Please fill in b 296-5545. Send	olanks, underline or one to WATER WEL	circle the correct ans L OWNER and retain	wers. Send top three n one for your record	e copies to Kansas De Is.	apartment :	