

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>NW 1/4 SE 1/4 NW 1/4</u>	<u>21</u>	T <u>27</u> S	R <u>1</u> <u>EDN</u>
Distance and direction from nearest town or city street address of well if located within city? <u>250 N. St. Francis Wichita KS Westside Factory B</u>					
2 WATER WELL OWNER:		SP-7			
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>30.5</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>14.5</u> ft. 2. <u>19.5</u> ft. 3. <u>19.5</u> ft.			
		WELL'S STATIC WATER LEVEL <u>19.5</u> ft. below land surface measured on mo/day/yr <u>8-9-93</u>			
		Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm			
		Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm			
		Bore Hole Diameter <u>8</u> in. to <u>31</u> in. and _____ in. to _____ ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Other (Specify below)</u> <u>Air Sparge Well</u>			
Was a chemical/bacteriological sample submitted to Department? Yes _____ No <u>X</u>		If yes, mo/day/yr sample was submitted _____			
Water Well Disinfected? Yes _____ No <u>X</u>					
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued _____ Clamped _____			
☒ Steel ☒ PVC 3 RMP (SR) 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)			
Blank casing diameter <u>2</u> in. to <u>90</u> ft., Dia <u>2</u> in. to <u>28.5</u> ft., Dia _____ in. to _____ ft.		Welded _____ Threaded _____			
Casing height above land surface <u>30</u> in., weight _____ lbs./ft. Wall thickness or gauge No. <u>5-640</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify) _____			
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped		8 Saw cut 11 None (open hole)			
SCREEN-PERFORATED INTERVALS: From <u>30.5</u> ft. to <u>28.5</u> ft., From _____ ft. to _____ ft.		9 Drilled holes			
GRAVEL PACK INTERVALS: From <u>31</u> ft. to <u>25</u> ft., From _____ ft. to _____ ft.		10 Other (specify) _____			
6 GROUT MATERIAL:		4 Other <u>570 Bentonite</u>			
Grout Intervals: From <u>25</u> ft. to <u>surface</u> ft., From _____ ft. to _____ ft.		10 Livestock pens 14 Abandoned water well			
What is the nearest source of possible contamination:		11 Fuel storage 15 Oil well/Gas well			
1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon ☒ Watertight sewer lines 6 Seepage pit 9 Feedyard		12 Fertilizer storage 16 Other (specify below)			
Direction from well? <u>West</u>		13 Insecticide storage			
		How many feet? <u>40</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	concrete			
0.5	5	silty CLAY			
5	7.5	sandy CLAY			
7.5	14.5	silty SAND fine			
14.5	30.5	SAND coarse to fine w/ trace of gravel			
30.5	31	silty CLAY olive green			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-9-93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>517</u> This Water Well Record was completed on (mo/day/yr) <u>8/12/93</u> under the business name of <u>Groundwater Tech Inc.</u> by (signature) <u>Albert Stout</u>					