

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>NE 1/4 SW 1/4 NW 1/4</u>	<u>21</u>	T <u>27</u> S	R <u>1</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>250 N. St. Francis Factory A westside</u>					
2 WATER WELL OWNER:		SAU-3W			
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>31</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>15</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>15</u> ft. below land surface measured on mo/day/yr <u>7-28-97</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8</u> in. to <u>31</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Air Spage Well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u> ; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes No <u>X</u>			
1 <u>Steel</u> 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded <u>X</u>			
Blank casing diameter <u>2</u> in. to <u>29</u> ft., Dia in. to ft.					
Casing height above land surface <u>30</u> in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 <u>Steel</u> 3 <u>Stainless steel</u> 2 Brass 4 Galvanized steel		5 Fiberglass 8 RMP (SR) 6 Concrete tile 9 ABS 11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 <u>Wire wrapped</u> 9 Drilled holes			
SCREEN-PERFORATED INTERVALS: From <u>31</u> ft. to <u>29</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>31</u> ft. to <u>25</u> ft., From ft. to ft.					
6 GROUT MATERIAL:		4 Other <u>4/57% bentonite</u>			
Grout Intervals: From <u>25</u> ft. to <u>surface</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 <u>Watertight sewer line</u> 6 Seepage pit 9 Feedyard		11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage			
Direction from well? <u>West</u>		How many feet? <u>40</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Concrete			
0.5	8.0	Silt, clay w/ fine SAND			
8	15	SAND med to fine			
15	15.3	clay lens			
15.3	32.0	SAND coarse to fine w/ trace of fine gravel			
32.0	33.0	CLAY Olive green.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-28-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>517</u> This Water Well Record was completed on (mo/day/yr) <u>8/18/97</u> under the business name of <u>Groundwater Tech Inc</u> by (signature) <u>Albert Stout</u>					