

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Salgwick</u>		<u>NW 1/4 SE 1/4 NW 1/4</u>	<u>21</u>	T <u>27</u> S	R <u>1</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>250 N. St Francis Wichita KS SAW-SE</u>					
2 WATER WELL OWNER: <u>The Coleman Company</u>					
RR#, St. Address, Box # : <u>250 N. St. Francis</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : <u>Wichita KS 67202</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>37</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>15</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>15.2</u> ft. below land surface measured on mo/day/yr <u>7-12-93</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8</u> in. to <u>35</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Air Sponse well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No <u>X</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded. <u>X</u>
Blank casing diameter <u>30 2</u> in. to <u>35</u> ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface <u>30</u> in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	<u>Wire wrapped</u>	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>37</u> ft. to <u>35</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>37</u> ft. to <u>32</u> ft., From ft. to ft.					
6 GROUT MATERIAL: <u>Neat cement</u> 2 Cement grout 3 Bentonite 4 Other <u>4/5% bentonite</u>					
Grout Intervals: From <u>32</u> ft. to <u>surface</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage <u>Abandoned fuel storage</u>	
Direction from well? <u>West</u>		How many feet? <u>50</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	concrete			
0.5	1.0	fill SAND			
1.0	2.0	pk brown, silty fine SAND			
2.0	7.0	Brown, silty fine SAND, trace CLAY			
7.0	8.0	Brown/gray sandy CLAY			
8.0	7.5	Brown, silty SAND, fine gravel & trace of red SAND & CLAY			
7.5	10	lt. brown, medium fine SAND, trace red			
10	15	lt. brown, sat., medium fine SAND, trace coarse SAND & fine gravel.			
15	37	lt. blue green, wet, silty CLAY			
37	37.5				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-12-93</u> and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. <u>517</u>		This Water Well Record was completed on (mo/day/yr) <u>8/12/93</u>			
under the business name of <u>Groundwater Tech Inc.</u>		by (signature) <u>Albert Stout</u>			