

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NE 1/4 NW 1/4 NW 1/4		Section Number 22	Township Number T 27 S	Range Number R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 1900 East Central, Latitude 37-41-36.328, Longitude 97-18-46.853						01948002 MW-8
2 WATER WELL OWNER: Western Resources						
RR#, St. Address, Box # : P.O. Box 889				Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Topeka, KS				Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 18.5 ft. ELEVATION: 1298.7				
		Depth(s) Groundwater Encountered 1. 13.5 ft. 2. 13.5 ft. 3. 13.5 ft.				
		WELL'S STATIC WATER LEVEL 15.0 ft. below land surface measured on mo/day/yr 02/04/94				
		Pump test data: Well water was NA ft. after NA hours pumping NA gpm				
		Est. Yield NA gpm: Well water was NA ft. after NA hours pumping NA gpm				
		Bore Hole Diameter 8.25 in. to 18.5 ft., and 18.5 in. to 18.5 ft.				
		WELL WATER TO BE USED AS:				
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes NA No X ; If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes NA No X				
5 TYPE OF BLANK CASING USED:						
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)
				7 Fiberglass		CASING JOINTS: Glued NA Clamped NA
						Welded NA
						Threaded X
Blank casing diameter 2 in. to 8.5 ft., Dia 2 in. to 8.5 ft., Dia 2 in. to 8.5 ft.		Casing height above land surface -3 in., weight NA lbs./ft. Wall thickness or gauge No. Sch 40				
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel		3 Stainless steel		5 Fiberglass		7 PVC
2 Brass		4 Galvanized steel		6 Concrete tile		10 Asbestos-cement
						11 Other (specify)
						12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut
2 Louvered shutter		4 Key punched		6 Wire wrapped		11 None (open hole)
				7 Torch cut		9 Drilled holes
						10 Other (specify)
SCREEN-PERFORATED INTERVALS:						
From 8.5 ft. to 18.5 ft.		From 8.5 ft. to 18.5 ft.		From 8.5 ft. to 18.5 ft.		From 8.5 ft. to 18.5 ft.
GRAVEL PACK INTERVALS:						
From 6.5 ft. to 18.5 ft.		From 6.5 ft. to 18.5 ft.		From 6.5 ft. to 18.5 ft.		From 6.5 ft. to 18.5 ft.
6 GROUT MATERIAL:						
1 Neat cement		2 Cement grout		3 Bentonite		4 Other
Grout Intervals: From 0 ft. to 4.5 ft., From 4.5 ft. to 6.5 ft., From 6.5 ft. to 18.5 ft.						
What is the nearest source of possible contamination:						
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens
2 Sewer lines		5 Cess pool		8 Sewage lagoon		14 Abandoned water well
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		11 Fuel storage
						15 Oil well/Gas well
						12 Fertilizer storage
						16 Other (specify below)
						13 Insecticide storage
						How many feet?
Direction from well?						
LITHOLOGIC LOG						
FROM	TO					
0	0.3	Asphalt				
0.3	5.0	Fat Clay; Dark Brown to Brown				
5.0	12.0	Silty Fat Clay; Brown				
12.0	13.5	Silt With Clay; Brown				
13.5	18.0	Fine to Coarse Sand; Brown				
PLUGGING INTERVALS						
FROM	TO					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/04/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 01/24/94 03/07/94 under the business name of Terracon Consultants, Inc. by (signature) <i>Steve R. Fisher</i>						