


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SE 1/4 SE 1/4 SW 1/4	25	T 27 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city?				50895013	
152' NW of the intersection of Harry Street & Edgemoor Street, Wichita, KS				Amoco No. 5114 MW-2	
2 WATER WELL OWNER: Groundwater Management Section, Amoco Oil Company					
RR#, St. Address, Box # : 7201 E. 38th Street, Space 7253				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : Tulsa, OK 74145				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 27 ft. ELEVATION: Approx. Surface Elev: 1325			
<div style="text-align: center;">N W E S 1 Mile 1/4</div> 		Depth(s) Groundwater Encountered 1. 20 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 15.3 ft. below land surface measured on mo/day/yr 02/21/89			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 27.5 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 2 in. to 12 ft., Dia		7 Fiberglass Welded			
Casing height above land surface -3 in., weight		Threaded X			
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS:		From 12 ft. to 27 ft., From ft. to ft.			
		From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From 9.5 ft. to 27.5 ft., From ft. to ft.			
		From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 0 ft. to 7.5 ft., From 7.5 ft. to 9.5 ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? WSW		How many feet? 13			
LITHOLOGIC LOG		PLUGGING INTERVALS			
FROM	TO			FROM	TO
0	4	Dark Brown Lean Silty Clay			
4	8	Red-Brown Lean Silty Clay			
8	19	Brown to Red-Brown Lean to Fat Silty Clay			
19	23	Olive-Green Fat to Lean Silty Clay			
23	27.5	Olive-Green Fat Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/19/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 3/28/89 under the business name of Terracon Consultants, Inc. by (signature) Long, D. D. Smith					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4