			WATE	R WELL RECORD				
		ER WELL:	Fraction			ction Number		
	Sedgwick		NW 1/4	NW 1/4 Inddress of well if locate	NW 1/4	25	Т 27	S R 1 (E)M
			-		-		g, Wichita, KS	52905021 S MW-3
			Oil Compan		1, 4007 1	. Kerrog	y, wichita, K	Amoco #9513
				ek Parkway, Blo	da 3 Si	ite 180	Board of Agric	ulture, Division of Water Resou
			and Park, K				_	
								Surface Elev: 1350
→ AN "X"	IN SECTION	BOX:						ft. 3
ī [<u>, 1 </u>	<u> </u>						/day/yr03/23/90
	x	i	i .					ours pumping
-	NW	NE	1	' ₄ _				ours pumping g
		i _						in. to
* w -	1	- E	1	TO BE USED AS:	5 Public wat			
7	1	1	1 Domestic	3 Feedlot	6 Oil field wa	ater supply	9 Dewatering	12 Other (Specify below)
	SW	2F	2 Irrigation	4 Industrial	7 Lawn and	garden only	10 Monitoring well	.,
			Was a chemical/	bacteriological sample	submitted to D	epartment? Y	esNoX	; If yes, mo/day/yr sample was s
	S		mitted			Wa	ater Well Disinfected?	Yes No X
5 TYPE	OF BLANK C	ASING USED:		5 Wrought iron	8 Conce	ete tile	CASING JOINTS	S: Glued Clamped
1 St		3 RMP (S	R)	6 Asbestos-Cement	9 Other	(specify belo		Welded
(2)P\	/C	4 ABS		7 Fiberglass				Threaded X
								in. to
				.in., weight	_		ft. Wall thickness or ga	auge NoSchedule .40
TYPE OF	SCREEN OF	R PERFORATIO	N MATERIAL:		(7)P\	/C	10 Asbesto	s-cement
1 Ste	eel	3 Stainles:	s steel	5 Fiberglass	8 RM	MP (SR)	11 Other (s	specify)
2 Br		4 Galvaniz		6 Concrete tile	9 A E	BS	12 None us	sed (open hole)
		ATION OPENIN		5 Gauz	ed wrapped		8 Saw cut	11 None (open hole)
	ontinuous slot		fill slot		wrapped		9 Drilled holes	
	uvered shutte		ey punched	7 Torch			` ' ' ' ' '	
SCREEN-	PERFORATE	D INTERVALS:						ft. to
	SDAVEL DAG	CK INTERVALS:						, , ft. to
	SHAVEL FAC	INTERVALS.	From	ft. to		π., Fro ft., Fro		
6 GROUT	Γ MATERIAL:	1 Neat		2)Cement grout	Rent/			11. 10
Grout Inter	rvals: Fron	10	ft to 6.0	ft From 6	.0 Obenic	to 7.0	ft From	ft. to
What is th	e nearest so	urce of possible	contamination:		_			14 Abandoned water well
		4 Later		7 Pit privy	_		storage	
2 Se	wer lines	5 Cess		8 Sewage lag			izer storage	16 Other (specify below)
3 Wa	atertight sewe	er lines 6 Seep	•	9 Feedyard			ticide storage	
Direction f		Northwest		•		How ma	ny feet? 20	
FROM	то	,	LITHOLOGIC	LOG	FROM	то		GING INTERVALS
0	.5	Concrete						
.5	.8	Fill: M	Medium Sand,	, Brown				
8	3.5			an to Fat Clay				
3.5	5.5		wn Lean to					
5.5	9.5			to Fat Clay				4.50
0 -	14.5		ay Lean to					
9.5	17.0		ay Fat Clay					The state of the s
14.5		1113 TTO C.	ay Lean to	rat Clay				
	20.0	OIIve-Gr						
14.5		OIIVe-Gr	5.77R			1	***************************************	
14.5		OIIVe=Gr						
14.5		OTIVE=Gr						
14.5		Olive-Gr						
14.5		Olive-Gr						
14.5		Olive-Gr						
14.5	20.0							
14.5 17.0	20.0	R LANDOWNER	R'S CERTIFICATI					ed under my jurisdiction and w
14.5 17.0	20.0 RACTOR'S O	R LANDOWNER	R'S CERTIFICATI	0		and this reco	ord is true to the best of	my knowledge and belief. Kans
14.5 17.0	20.0 RACTOR'S O	R LANDOWNER	R'S CERTIFICATI 03/15/9 416	O This Water W	/ell Record wa	and this reco	ord is true to the best of	
14.5 17.0 7 CONTF completed Water Wel under the	RACTOR'S O on (mo/day/y) I Contractor's business name	R LANDOWNER /ear)	R'S CERTIFICATI 03/15/9 416 	0 This Water Won Consultants	/ell Record wa	and this reco as completed by (signa	ord is true to the best of on (mo/day/yr)	my knowledge and belief. Kans