

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>SEDGWICK</u>	<u>SEE</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>S</u> $\frac{1}{4}$	<u>25</u>	T <u>27</u> S	R <u>1</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

45' from corner of HARRY & EDMOND - MW-13

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>P.O. Box 26045</u>	Application Number:
City, State, ZIP Code : <u>SHAWNEE Mission, KS 66225</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>20</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>14</u> ft. below land surface measured on mo/day/yr <u>12-13-90</u>
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter in. to ft., and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... ☒ If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes ☒ No ☐	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>2.0</u> in. to ft., Dia. in. to ft., Dia. in. to ft.			
Casing height above land surface: <u>2</u> (FLUSH) in., weight lbs./ft. Wall thickness or gauge No. <u>40</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	2 Mill slot	3 Gauzed wrapped	4 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From <u>20</u> ft. to <u>10</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS:			
From <u>20</u> ft. to <u>8</u> ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: <u>3</u> From <u>8</u> ft. to <u>6</u> ft., <u>2</u> From <u>6</u> ft. to <u>0</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>E</u>				
How many feet? <u>40</u>				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>15</u>	<u>ASPHALT</u>			
<u>.5</u>	<u>14</u>	<u>CLAY - SILTY</u>			
<u>14</u>	<u>20</u>	<u>CLAY</u>			
GROUT VARIANCE GRANTED CASING VARIANCE GRANTED					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>1</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12-14-19</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>517</u> This Water Well Record was completed on (mo/day/yr) <u>12-13-90</u> under the business name of <u>GROUNWATER TECHNOLOGY, INC</u> by (signature) <u>Albert</u>
