	WATE	R WELL RECOP	RD Form WY	/C-5 KSA	82a-1212		R-2	_		
1 LOCATION OF WATER WELL:	Fraction			Section Num	ber 1	Township Nu	umber	Range Nu	umber	
County: <u>Sedgewick</u>	SW 1/4	SW 1/4	SW 1/4	_26	т	27	S	R 1	<u> a</u> w	
Distance and direction from nearest towr	or city street a	ddress of well if	located within c	ty?						
3216 E. Harry wich	ita, Kansa	IS								
2 WATER WELL OWNER: Quik T	rip Corp.									
RR#, St. Address, Box # : 901 N.	Mingo					Board of A	griculture, (Division of Wate	r Resources	
City, State, ZIP Code : Tulsa,	<u>Oklahoma</u>					Application	Number:			
3 LOCATE WELL'S LOCATION WITH 4	DEPTH OF C	OMPLETED WE				(site) 54.0			
	_ Depth(s) Ground	water Encounter	ed 138.1)	. ft. 2		ft. 3		ft.	
	NELL'S STATIC	WATER LEVEL		ft. below land	surface m	neasured on	mo/day/yr			
	Pum	o test data: We	Il water was		ft. after		hours pu	mping	gp m	
NW NE	Est. Yield	. gpm: We	ell water was		ft. after		hours pu	mping	gpm	
	Bore Hole Diame	eter 15.0	in. to 45.	5	.ft., and		.in	. to	ft.	
	WELL WATER 1	O BE USED AS	S: (5 Public	water supply						
	1 Domestic	3 Feedlot	ь Oil fiel	water supply	y 9 Dev	vatering	2	Other (Specify I	below)	
SW SE	2 Irrigation	4 Industri	al 7 Lawn a	ind garden or	nly 10 Mo	nitoring well	R	ecovery		
	Was a chemical/	bacteriological sa	ample submitted	to Departmen	t? Yes	No	; If yes	, mo/day/yr sam	ple was sub	
L S	mitted				Water We	II Disinfecte	d? Yes	No		
5 TYPE OF BLANK CASING USED:		5 Wrought iror	n 8C	oncrete tile	C	CASING JOI	NTS: Glue	dClamp	ed	
1_Steel 3 RMP (SR)	6 Asbestos-Ce		· · ·				ed		
2 PVC 4 ABS		7 Fiberglass					Threa	aded		
Blank casing diameter 8.0i	n. to	ft., Dia		n. to	ft.,	Dia		in. to	ft.	
Casing height above land surface24	.0	.in., weight4	1.0		lbs./ft. Wal	I thickness of	or gauge N	o. Sch. 40		
TYPE OF SCREEN OR PERFORATION	MATERIAL:		7	PVC		10 Asb	estos-ceme	ent		
1 Steel 3 Stainless	steel	5 Fiberglass	8	RMP (SR)		11 Oth	er (specify)			
2 Brass 4 Galvanize	d steel	6 Concrete tile	. 9	ABS		12 Nor	ne used (op	en hole)		
SCREEN OR PERFORATION OPENING	S ARE:	5	Gauzed wrapp	ed	8 Sa	aw cut		11 None (ope	n hole)	
1 Continuous slot 3 Mill slot		6		9 Di	rilled holes					
2 Louvered shutter 4 Key	y punched		Torch cut							
SCREEN-PERFORATED INTERVALS:	From. 45.	O ft	t. to 15 ") ft.,	From		ft. t	o	ft.	
		<i>.</i> ft								
GRAVEL PACK INTERVALS:	From45.	Qft								
	From		to					0		
		2 Cement grout								
Grout Intervals: From	t. to 8 .0	ft., From								
What is the nearest source of possible 23 Araminaten:								14 Abandoned water well		
1 Septic tank 4 Lateral lines		7 Pit privy			11 Fuel storage			15 Oil well/Gas well		
2 Sewer lines 5 Cess pool		8 Sewage lagoon			12 Fertilizer storage			16 Other (specify below)		
3 Watertight sewer lines 6 Seepa	ige pit	9 Feedy	ard		nsecticide :	-		•••••		
Direction from well? South	LITHOLOGIC	100	FRO		many feet	<u>'? 100 '</u>	LIGGING I	NTERVALS		
FROM TO		100						INTERIVALS		
0.0 24.0 Stiff br	•									
24.0 45.0 Loose br	own silty	sanc								
						· · · · · · ·				
		* * manual * * ***								
			I	I						
7 CONTRACTOR'S OR LANDOWNER	S CERTIFICAT	ION: This water	well was (1) co	nstructed, (2)	reconstruc	ted, or (3) p	olugged und	per my jurisdicti	on and was	
completed on (mo/day/year)	/91			and this	record is tr				mer. Kansas	
Water Well Contractor's License No						ayyry	929/5	176		
under the business name of JSR	Drilling-	Services,	Inc.		ignature)	y og	won	9	····	
INSTRUCTIONS: Use typewriter or ball point p of Health and Environment, Bureau of Water,	en. <u>PLEASE PRESS</u> Topeka, Kansas 6662	<u>CIRMLY</u> and <u>PRINT</u> c 20-7320. Telephone: 9	13-296-5545. Send c	ne to WATER WE	ELL OWNER a	and retain one f	or your record	s.	partment	