

1 LOCATION OF WATER WELL:		Fraction NW 1/4 SW 1/4 NW 1/4		Section Number 27	Township Number T 27 S	Range Number R 1 E
County: Sedgwick						
Distance and direction from nearest town or city street address of well if located within city? 30' South & 210' East of Intersection of Gilbert & Hydraulic, Wichita, Kansas 01948011 MW-2						
2 WATER WELL OWNER: Blair House Apartments						
RR#, St. Address, Box #: 888 South Hydraulic				Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: Wichita, Kansas 67211				Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 23.5 ft. ELEVATION: Approx. Surface Elev.: 99.1				
		Depth(s) Groundwater Encountered 1. 11.0 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 15.56 ft. below land surface measured on mo/day/yr 05/06/94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9.0 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X				
		5 TYPE OF BLANK CASING USED:				
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 8.5 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)				
		SCREEN-PERFORATED INTERVALS: From 8.5 ft. to 23.5 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 7.0 ft. to 23.5 ft., From ft. to ft. From ft. to ft., From ft. to ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 0.0 ft. to 6.0 ft., From 6.0 ft. to 7.0 ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage						
Direction from well? How many feet?						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0.0	1.0	Fill: Asphalt & Gravel				
1.0	6.0	Fill: Silty Lean Clay; Dark Brown				
6.0	8.0	Silty Lean Clay; Brown				
8.0	10.0	Silty, Sandy Lean Clay; Light Brown, Trace Gravel				
10.0	11.0	Silty Fat Clay; Gray-Brown				
11.0	23.0	Silty, Fine to Medium Sand; Brown				
23.0	23.5	Clayey Shale; Gray				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05/06/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 6-7-94 under the business name of Terracon Consultants, Inc. by (signature) Steve Fischer						