1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number
Sedgwick	SW 1/4	NE 1/4 N	E 1/4	29	27	R 1E FAW
Distance and direction frem nearest town or ci		77.15		2,5	T 21 s	R IE EW
<u>'</u>						
Hwy 54 and Water Street Wichita, Kansas						
	Y OF WICHIT	A			Parad of Academic P	N. L. J. W. L. D
	. Box 9163					ivivsion of Water Resource
CITY, STATE, ZIP CODE: Wic	hita, Kansa			67277	Application Number	r:
3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION:						
Depth(s) groundwater Encountered 1 R. 2 ft. 3 ft.						
	ı	ATER LEVEL 15	FT.	BELOW LAND SU	RFACE MEASURED ON modday/yr	03/28/1994
NWNX	Pump tes	t data: Well wa	iter was	ft.	after hours pun	ıping gpm
	Est. Yield	gpm: Well w	ater was	ft.	after hours pun	ıp in g gpm
W W E	Bore Hole Diameter		0	ft.	and in.	to ft.
-	WELL WATER 40	BE USED AS: 5	Public wate	r supply		njection well
sw se	1 Domestic		Oil field wa			Other (Specify below)
	2 Irrigation	4 Industrial 7	Lawn and g	garden only	10 Monitoring well	
	Was a chemical/bacte	riological sample sub	mitted to De	epartment? Yes	No 🗶 ; If yes, n	no/day/yr sample was
S submitted Water Well Disinfected? Yes X No						
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped						
1 Steel 3 RMP (SR)		6 Asbestos-Cement	9	Other (Specify l	•	Velded
2 PVC 4 ABS 7 Fiberglass Threaded						
Blank casing Plameter 8	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height above land surface		weight		lbs. / ft.	Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORA	7 PVC			10 Asbestos-cem		
1 Steel 3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify	
2 Brass 4 Galvanized ste	el	6 Concrete tile	9	O ABS	12 None used (o	pen hole)
SCREEN OR PERFORATION OP	ENING ARE:	5 Gauze	d wrapped		8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill s	6 Wire wrapped			9 Drilled holes		
2 Louvered shutter 4 Key p	7 Torch	cut		10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from ft. to ft., From ft. to					ft.	
	from	ft.		•		ft.
GRAVEL PACK INTER		ft.		ft., Fro ft., Fro		ft.
from		•		ft., Fro		1L.
6 GROUT MATERIAL: 1 Neat		Cement grout		ntonite		hole plug
Grout Intervals: From 3	ft. to 15					
What is the nearest source of possible contamination:		ft. From ft. to		10 Livest	ft. From ock pens 14	ft. to ft. Abandon water well
1 Septic tank 4 Lateral lines				11 Fuel s	1471billion water wen	
2 Sewer lines 5 Cess pool				12 Fertil	tilizer storage 16 Other (specify below)	
0.000	9 Feedyard	12 Turnethalds atomore				
Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS						
			0	3	surface materia	
			3	15	bentonite hole	
			15	40	chlorinated sar	
	44-44-44-44				44	
						Methodological Policy Control of the
					WW.	
	4-1/					
					MANAGE CONTRACTOR OF THE PROPERTY OF THE PROPE	
					4644	
		·				
7 CONTRACTOR'S OR LANDOWN	ER'S CERTIFICATION: Th	is water well was (1) construct	ed, (2) reconst	ructed, or (3) <u>plugge</u> d under i	ny jurisdiction and
was completed on (mo/day/year)						
Well Contractor's License No						
Under the business name of Harp Well & Pump Service. Inc. by (signature)						
Jane Frederick						

Ŧ