1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number		T
LJ					Township Number	Range Number
Sedgwick	SW 1/4	NE 1/4 N	E 1/4	29		R 1E EW
Distance and direction frem nearest tow	vn or city street address of well if loca	ited within city?				
Hwy 54 and Wa	ater Street	Wichit	a, Ka	nsas		
2 WATER WELL OWNER: C	ITY OF WICHIT	'A				
RR#, ST. ADRESS, BOX#: P	O. Box 9163				Board of Agriculture, E	lvivsion of Water Resource
1	Michita, Kansa	s,		67277	Application Number	er:
J LOCATE WELL'S LOCATION WIT		A WELL	40		EVATION:	
AN "X" IN SECTION BOX:	Depth(s) groundw		1	n. Ez	2 ft.	3 ft.
	<del></del>		_		URFACE MEASURED ON mo/day/yr	
		ATER LEVEL 15			• •	03/28/1994
NWND-	Pump tes		ater was	n.	after hours pun	rping gpm
	Est. Yield	gpm: Well w	ater was	Ո.	after hours pun	n <b>ping gp</b> m
Bw	E Bore Hole Diameter	5	0	ſt.	and in.	to ft.
-	WELL WATER TO	HE USED AS: 5	Public wate	r supply	8 Air conditioning 11 l	njection well
SWSE	1 Domestic	3 Feedlot 6	Oil field wa	ter supply	9 Dewatering 12 0	Other (Specify below)
	2 Irrigation	4 Industrial 7	Lawn and g	arden only	10 Monitoring weli	
	Was a chemical/bacte	eriological sample sub	mitted to D	epartment? Yes	No X; If yes, n	no/day/yr sample was
s	submitted			-	nter Well Disinfected? Yes	• •
TURE OF CASING HOPE						
S WI OUGHT HOR O CONCINCT THE CHARLES						Aueu Champea Welded
2 PVC 4 ABS		7 Fiberglass	,	Janes (opening	•	rveiueu Threaded
Blank casing Diameter 8 Casing height above land surfa	in. to	ft., Dia	in.		ft., Dia in.	to ft.
TYPE OF SCREEN OR PERF		weight	,	lbs. / ft. / PVC	Wall thickness or gauge No. 10 Asbestos-cem	ent
		5 Fiberglass		RMP (SR)		
1 Steel 3 Stainless		-		` '	11 other (specif	
2 Brass 4 Galvanize	ed steel	6 Concrete tile		ABS	12 None used (o	•
SCREEN OR PERFORATION	5 Gauzed wrapped			8 Saw cut	11 None (open hole)	
1 Continous slot 3	6 Wire wrapped			9 Drilled holes		
2 Louvered shutter 4	7 Torch	cut		10 Other (specify)		
SCREEN-PERFORATION IN	TERVALS: from	r.		ft., Fro		n.
				•		
from		ft. to		ft., From		ft.
GRAVEL PACK INTERVALS: from		ft. to		ft., Fro		ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hent on its hole plug						
		ement grout	3 Be	ntonite	4 Other bentonite	e hole plug
Grout Intervals: From 3	ft. to 15	ft. From	ft.		ft. From	ft. to ft.
What is the nearest source of possible contamination:					Abandon water well	
1 Septic tank 4 Lateral lines					el storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool					izer storage 16	Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent						
Direction from well? How many feet?						
FROM TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTE	RVALS
			0	3	surface materia	
			3	15	bentonite hole	
			15	40	chlorinated sar	
			1			
			1			
			-			
						<u> </u>
7	···		<del></del>			
7 CONTRACTOR'S OR LAND	OWNER'S CERTIFICATION: Th	is water well was (1	construct	ed, (2) reconst	ructed, or (3) <u>plugged</u> under ı	ny jurisdiction and
was completed on (mo/day/year)						
Well Contractor's License !	No4.3.0	This Water Well Re	cord was c	ompleted on (r	no/day/yr)	0/94
Under the business name of Harp Well & Pump Service Inc by (signature)						
Jane Frederick						
t .						