


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction NE 1/4 SE 1/4 NW 1/4	Section Number 29	Township Number T27 S	Range Number R 1 E
Distance and direction from nearest town or city street address of well if located within city? 1150 FT S. OF 508 DAYTON WEST HIGH SCHOOL B-12					
2 WATER WELL OWNER: UNIFIED SCHOOL DIST #259 RR#, St. Address, Box #: 3850 N HYDRAULIC City, State, ZIP Code: WICHITA KS 67219			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;">  </div>		4 DEPTH OF COMPLETED WELL: 23 ft. ELEVATION: 105.38 Depth(s) Groundwater Encountered 1. 14.5 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 15'10" ft. below land surface measured on mo/day/yr 2-21-90 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: <div style="display: flex; justify-content: space-between;"> <div> 1 Domestic 2 Irrigation </div> <div> 3 Feedlot 4 Industrial </div> <div> 5 Public water supply 6 Oil field water supply 7 Lawn and garden only </div> <div> 8 Air conditioning 9 Dewatering 10 Monitoring well </div> <div> 11 Injection well 12 Other (Specify below) </div> </div> Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: <div style="display: flex; justify-content: space-between;"> <div> 1 Steel 2 PVC Blank casing diameter 2 in. to 13 ft., Dia 2.614 in., weight lbs./ft. Wall thickness or gauge No. </div> <div> 3 RMP (SR) 4 ABS TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter SCREEN-PERFORATED INTERVALS: From 23 ft. to 13 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 23 ft. to 8' ft., From ft. to ft. </div> <div> 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) </div> <div> CASING JOINTS: Glued Clamped Welded Threaded 8 Concrete tile 9 Other (specify below) 10 Gauzed wrapped 11 None (open hole) </div> </div>					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 6 ft., From 6 ft. to 0 ft., From ft. to ft. What is the nearest source of possible contamination: <div style="display: flex; justify-content: space-between;"> <div> 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit </div> <div> 7 Pit privy 8 Sewage lagoon 9 Feedyard </div> <div> 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage </div> <div> 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) </div> </div> Direction from well? NW How many feet? 60					
FROM		TO		LITHOLOGIC LOG	
0		3		Silty to SANDY CLAY	
3		23		FINE TO COARSE SAND	
FROM		TO		PLUGGING INTERVALS	
0		6		CEMENT	
6		8		BENTONITE	
8		23		SAND	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-20-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 524 This Water Well Record was completed on (mo/day/yr) 2-26-90 under the business name of ALLIED LABS by (signature) <i>Richard J. [Signature]</i>					