

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SW 1/4 NE 1/4 SW 1/4	29	T 27 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 6' W of 1310 South Osage, Wichita, KS 52905026 MW-2					
2 WATER WELL OWNER: Mid-Am Building Supply, Inc. RR#, St. Address, Box #: 5705 North Broadway City, State, ZIP Code: Wichita, KS 67219 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24.5 ft. ELEVATION: Approx. Surface Elev: 1290			
<div style="text-align: center;"><p>1 Mile</p></div>		Depth(s) Groundwater Encountered 1. 18 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 15.6 ft. below land surface measured on mo/day/yr 03/19/90			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 9 in. to 25 ft., and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
Blank casing diameter 2 in. to 9.5 ft., Dia		7 Fiberglass		Threaded X	
Casing height above land surface 31 in., weight		lbs./ft. Wall thickness or gauge No. Schedule 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		7 PVC 10 Asbestos-cement		11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		6 Wire wrapped 9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 9.5 ft. to 24.5 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 8 ft. to 25 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 5 ft., From 5 ft. to 8 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? West How many feet? 100					
FROM TO LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS	
0	8"	Asphalt			
8"	2.0	Lean Clay with Sand, Dark Brown			
2.0	5.5	Lean Sandy Clay, Light Brown			
5.5	18.5	Fine to Medium Sand, Trace of Coarse Sand, Light Brown			
18.5	25.0	Medium to Coarse Sand with Gravel, Brown			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03/19/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 03/19/99 under the business name of Terracon Consultants, Inc. by (signature) <i>Steve Fischer</i>					