LOCATION OF BUILDING	EDACTION	Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCATION OF WATER WELL:	FRACTION			Section Number	Township Number	Range Number
Sedgwick	NW 1/4	SE 1/4 SE	E 1/4	31	т 27 в	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?						
2211 S. Elizabeth Wichita, Kansas						
	TT, Jim	a, Kansus				
	S. Elizabe				Board of Agriculture, D	ivivsion of Water Resource
	ta, Kansas				Application Number	r:
AN "X" IN SECTION BOX:	DEPTH OF COM		24		EVATION:	
N N	Depth(s) groundwa	ter Encountered	1	ft.	2 ft.	3 ft.
	ELL'S STATIC WA	ATER LEVEL 11	FT.	. BELOW LAND SUI	RFACE MEASURED ON mo/day/yr	07/19/1993
NWNE	Pump test	data: Well wa	ater was	ft.	after hours pum	iping gpm
Est	t. Yield	gpm: Well wa	ater was		after hours pum	
	re IIole Diamete WA	81		ft.,	and in.	to ft.
E W						njection weli
	ELL WATER TOB		Public water			njection weil Other (Specify below)
sig	1 Domestic		Oll field wa		· · · · · · · · · · · · · · · · ·	Miler (Specify Delow)
	2 Irrigation		Lawn and g		10 Monitoring well	
	as a chemical/bacter	riological sample subr	mitted to De	epartment? Yes	No 🗶 ; If yes, m	10/day/yr sample was
S	ubmitted			Wat	ter Well Disinfected? Yes	X No
5 TYPE OF CASING USED:		5 Wrought iron	8	Concrete tile	CASING JOINTS: G	lued Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Cement		Other (Specify b	•	Velded
2 PVC 4 ABS		7 Fiberglass		Other (open, 2	,	hreaded
		9				
Blank casing Dlaneter 1/4 in.	. to	ft., Dia	in.		ft., Dia in.	to ft.
Casing height above land surface 36	in.,	weight			Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATIO	ON MATERIAL:			7 PVC	10 Asbestos-ceme	ent
1 Steel 3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (specify	9
2 Brass 4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (or	oen hole)
SCREEN OR PERFORATION OPENIS	NC ADE.	5 Cauze	d wrapped		8 Saw cut	11 None (open hole)
145 4 1	NG ARE.	6 Wire w			9 Drilled holes	** 1.0m (-F,
o will slot	- •					
2 Louvered shutter 4 Key punch		7 Torch c	cut		10 Other (specify)	
SCREEN-PERFORATION INTERVAL	S: from	ft. to	ю.	ft., From	ft. to	ft.
	from	ft. t	ło	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS: from		ft. to		ft., Fron		ſt.
	from	ft. t		ft., Fron		ft.
6 GROUT MATERIAL: 1 Neat cem		ement grout		ntonite	4 Other	
	t. to 11					
· -		ft., From	ft.		ft., From	ft. to ft.
What is the nearest source of possible contamination:				10 Livesto	not store	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuei st	130	Oil well/Gas well
2 Sewer lines 5 Cess poo	əl	8 Sewage lagoor	8 Sewage lagoon			Other (specify below)
3 Watertight sewer lines 6 Seepage	pit	9 Feedyard		13 Insecticide storage		
Direction from well? Southeas	-	_			How many feet? 16	
	HOLOGIC LOG		FROM	то	PLUGGING INTE	PVALS
	Mozosas		O		surface soil	NYALO.
	7.12		1		cement grout	
			1 1 -			7 3 1
			11	24	chlorinated san	d and graver
	1					
7 CONTRACTOR'S OR LANDOWNER'S C	ERTIFICATION: This	s water well was (1)	constructe	ed, (2) reconstrı	ucted, or (3) <u>plugged</u> under n	ny jurisdiction and
was completed on (mo/day/year)						
Well Contractor's License No2	236т	This Water Well Rec	cord was co	ompleted on (m	o/day/yr)	
Under the business name ofHarj	o Well & J	Pump Servi	ce, Ix	າຕ by (sign	-41	
601					fane F	rederick
nui					A	