

1 LOCATION OF WATER WELL: County: Seagovick Fraction: NW 1/4 SE 1/4 SE 1/4 Section Number: 31 Township Number: T 27 S Range Number: R 1 E

Distance and direction from nearest town or city street address of well if located within city?
2236 S. Elizabeth

2 WATER WELL OWNER: my McCalister Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 2236 S. Elizabeth Application Number: none
City, State, ZIP Code: Wichita Kan 67213

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: 1300
Depth(s) Groundwater Encountered 1. 16 ft. 2. 15 ft. 3. 15 ft.
WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 9 ft. after 16 hours pumping 1300 gpm
Est. Yield 9 gpm: Well water was 16 ft. after 16 hours pumping 1300 gpm
Bore Hole Diameter 9 in. to 16 ft. and 16 in. to 16 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 0 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped X Welded X Threaded X
Blank casing diameter 5.56 in. to 25 ft., Dia 12 in. to 25 ft., Dia 12 in. to 25 ft., Dia 12 in. to 25 ft.
Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No. 26
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 25 ft. to 35 ft., From 25 ft. to 35 ft., From 25 ft. to 35 ft., From 25 ft. to 35 ft.
GRAVEL PACK INTERVALS: From none ft. to none ft., From none ft. to none ft., From none ft. to none ft., From none ft. to none ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 16 ft., From 0 ft. to 16 ft., From 0 ft. to 16 ft., From 0 ft. to 16 ft.
What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
Direction from well? East How many feet? 12

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Top Soil			
8	16	Fine Tan Sand			
16	35	Coarse Tan Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-6-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 473 This Water Well Record was completed on (mo/day/yr) 6-6-89 under the business name of Bearden Pump & Well Ser by (signature) David R. Bech