LOCATI	ION OF WA	FED WELL.	FRACTION	Water	r Well Record	Form WWC-5	KSA 82a-1212 Section Number	T T N N N N N N N N N N N N N N N N N N	I Para Namba	
				NT-				Township Number	Range Number	
_	Sedgw		NW 1/4			E 1/4	31		R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?										
2016 S. Elizabeth Wichita, Kansas 2 WATER WELL OWNER: SENECA VILLAGE ADAPTMENTS										
Danson Vidence Hinkingaid										
RR#, ST. ADRESS, BOX#: 2016 S. Elizabeth Board of Agriculture, Divivision of Water Resource										
	STATE, ZIP		ita, Kans					Application Number	st:	
	E WELL'S LO IN SECTION		DEPTH OF CO			40		EVATION:	2	
+ г		N	Depth(s) ground			1	ft.	2 ft.	3 ft.	
$\sqcup \sqcup$			WELL'S STATIC			•		RFACE MEASURED ON mo/day/yr	02/01/1994	
'	NW	NE	•	est data:		water was		after hours pun		
<u> </u>		1 1 1	Est. Yield	gpm:		water was		after hours pun		
M Mile		X	Bore Hole Diamete		in.	to 40	ft.	and in.	to ft.	
			WELL WATER TO			5 Public wate			injection well	
1 1 }	sw	sie	1 Domestic	3 Feedlo		6 Oil field wa			Other (Specify below)	
			2 Irrigation	4 Indust		7 Lawn and g	<u> </u>	10 Monitoring well		
+ 1		S	Was a chemical/bac	cteriological :	sample su	bmitted to De	-		no/day/yr sample was	
submitted water weil Distiniected: Yes X No										
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped										
1 Steel		3 RMP (SR)			tos-Cemei 		Other (Specify b	•	Velded	
2 PVC		4 ABS		7 Fiberg		_	DR-26		Threaded	
Blank casing Diameter 5 in. to 20 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No										
			2 in. TON MATERIAL:		weight 2			Wall thickness or gauge No. 10 Asbestos-cem	.214	
1 Steel		3 Stainless Steel	ION MAI ERIAL:	: 5 Fibergl	lass		PVC RMP (SR)	11 other (specify		
2 Brass		4 Galvanized steel	1	6 Concre			ABS	•		
				Concre			ADS	12 None used (o)	·	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes										
		3 Mill slo	_							
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-	-PERFOR	ATION INTERVA	ALS: from 2	0	ft.	to 40	ft., From	ft. to	ft.	
			from			to	ft., From		ft.	
GRAVEL PACK INTERVALS: from 20				20	ft. to 40		ft., Fron		ft.	
CROI	IT MADE	DYLY 1 Nort o	from 2	10		to	ft., Fron		ft	
6 GROU			_	Cement gro	_		ntonite	4 Other		
Grout Inte		_	ft. to 20	ft. F	ronı	ft.		ft. From	ft. to ft.	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines					7 Pit privy		10 Livesto 11 Fuel ste		Abandon water well	
							- 15	15 Oil well/Gas well		
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify belo								Ther (specify below)		
5 waterught sewer lines 6 Seepage pit 9 reedyard										
Direction from well? North FROM TO LITHOLOGIC LOG					I EDOM I			How many feet? 50 TO PLUGGING INTERVALS		
	2	topsoil	AT HOLOGIC LO	<u> </u>		FROM	10	PLUGGING INTE	KVALS	
	5	sandy cla	av			<u> </u>	· 			
	39		o coarse	sand						
		and grave		Juna	· · · · · · · · · · · · · · · · · · ·					
39	40	blue sha								
									Ministration and American State of the Control of t	
								The same of the sa	1711 1	
								- Allerian		
								1,100		
			444							
7 CONTRACTORIS ON ANNOUNCED CONTROL This water well was (4) constructed (9) reconstructed as (9) religion of the second condensation and										
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)										
Well Contractor's License No236										
	Under the business name of HarpWell&PumpService./Inc by (signature)									
		Villanta	-					Jane of	rederick	
								************	22000	