

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SW 1/4 NE 1/4 NE 1/4		32		T 27 S		R 1 <b>EW</b>	
Distance and direction from nearest town or city street address of well if located within city?									
1650 S. Water Wichita KS									
2 WATER WELL OWNER: City of Wichita									
RR#, St. Address, Box # : 1900 E. 9th Street						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Wichita KS 67214						Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 26.3 ft. ELEVATION: N.A.							
		Depth(s) Groundwater Encountered 1. 18.5 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL: N.A. ft. below land surface measured on mo/day/yr							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter: 11 in. to ft. and in. to ft.							
		WELL WATER TO BE USED AS:							
		1 Domestic		3 Feedlot		6 Oil field water supply		8 Air conditioning	
		2 Irrigation		4 Industrial		7 Lawn and garden only		11 Injection well	
								12 Other (Specify below)	
								<b>10 Monitoring well</b>	
Was a chemical/bacteriological sample submitted to Department? Yes. No. XX. If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes No XX									
5 TYPE OF BLANK CASING USED:									
1 Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below)		CASING JOINTS: Glued Clamped	
<b>2 PVC</b>		4 ABS		7 Fiberglass				Welded Threaded Flush	
Blank casing diameter: 4 in. to ft. Dia. in. to ft. Dia. in. to ft.									
Casing height above land surface: in., weight: 2 lbs./ft. Wall thickness or gauge No. 25									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)		10 Asbestos-cement	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS		11 Other (specify)	
								12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot		<b>3 Mill slot</b>		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes			
				7 Torch cut		10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 15.3 ft. to 26.3 ft. From ft. to ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 13.6 ft. to 26.3 ft. From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 <b>Cement grout</b> 3 Bentonite 4 Other									
Grout Intervals: From 13.6 ft. to 11.8 ft. From 11.8 ft. to 1.0 ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens		14 Abandoned water well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage		15 Oil well/Gas well	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage		<b>16 Other (specify below)</b>	
						13 Insecticide storage		still checking	
Direction from well? How many feet?									
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0.5	7.1	Silty sandy clay.							
7.1	8.5	Fine to medium sand.							
8.5	13.5	Fine to very coarse sand.							
13.5	17.5	Fine to medium sand.							
17.5	26.3	Fine to very coarse sand.							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <b>(1) constructed</b> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-27-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 12-31-91 under the business name of GSI by (signature) Allison Irwin									