

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		NE 1/4 NE 1/4 NE 1/4	33	T 27 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city?					
1515 E. Harry Wichita					
2 WATER WELL OWNER: City of Wichita					
RR#, St. Address, Box # : 1900 E. 9th Street					
City, State, ZIP Code : Wichita KS 67214					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 24.0 ft. ELEVATION: N.A.			
		Depth(s) Groundwater Encountered 1. 17.5 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL: N.A. ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 11 in. to ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No XX					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC		4 ABS	7 Fiberglass		Threaded Flush
Blank casing diameter 4 in. to ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface Flush in. weight 2 lbs./ft. Wall thickness or gauge No. 25"					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 14.0 ft. to 24.0 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 10.3 ft. to 24.0 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 10.3 ft. to 8.0 ft. From 8.0 ft. to 1.0 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	Still Checking
Direction from well? How many feet?					
FROM TO		LITHOLOGIC LOG	FROM TO	PLUGGING INTERVALS	
0.0	0.2	Asphalt.			
0.2	2.0	Sand, silty & clay fill.			
2.0	4.5	silty fine sand.			
4.5	6.0	Silty sandy clay.			
6.0	24.0	Sand.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-6-91 and this record is true to the best of my knowledge and belief. Kansas Water Contractor's License No. 531. This Water Well Record was completed on (mo/day/yr) 1-10-92 under the business name of by (signature) <i>Alison Irwin</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					