			WAT	ER WELL RECORD	Form W	NC-5 KSA 828	a-12 <u>1</u> 2			
1 LOCATIO	ON OF WAT	ER WELL:	Fraction			Section Number			Range N	$\overline{}$
County: S	Sedgwick		SE 1		NE 1/4		т 27	S	R 1	(E)V
				address of well if local						
150	South			30 South Laura	Street	t, Wichita,	KS 5	2905020	LWMW-2	
	R WELL OW		-	/ Airplanes						
RR#, St.	Address, Box	x#: P. O.	Box 7730	M/S K11-65			Board of	f Agriculture, I	Division of Wate	er Resource
	, ZIP Code		ta, KS 6					ion Number:	·····	
J LOCATI	E WELL'S L IN SECTION	OCATION WITH N BOX:	Depth(s) Grour	COMPLETED WELL	1 2.	l ft.	2	ft. 3	3	ft.
Ŧ [C WATER LEVEL						
-	NW	*NE	Est. YieldN.	np test data: Well wa A gpm: Well wa	ter was .	ft. a	after	hours pu	ımping	gpm
. w ⊢		E		neter1.1in. t	032,	P			. to	
₹	!			TO BE USED AS:		water supply	8 Air condition	•	Injection well	
1 -	- SW	SE	1 Domesti				9 Dewatering			
	1	ī	2 Irrigation			and garden only	ullet			
↓ L			Was a chemica	l/bacteriological sample	submitted	to Department? Y	'esNo	X; If yes	, mo/day/yr sam	ple was sub
-		<u> </u>	mitted			Wa	ater Well Disinfe	cted? Yes	No X	ζ
5 TYPE (OF BLANK (CASING USED:		5 Wrought iron	8 C	concrete tile	CASING .	JOINTS: Glue	d Clamp	oed
1 Ste		3 RMP (SI	₹)	6 Asbestos-Cemen	t 9 C	other (specify below	w)	Weld	ed	
2 PV		4 ABS		7 Fiberglass					adedX	
				ft., Dia						
Casing hei	ight above la	and surface	30.4	in., weight			ft. Wall thicknes	ss or gauge N	_{o.} Schedul	.e 40
TYPE OF	SCREEN O	R PERFORATIO	N MATERIAL:		(7) PVC	10 A	Asbestos-ceme	ent	
1 Ste	eel	3 Stainless	steel	5 Fiberglass	7	RMP (SR)	11 (Other (specify)		
2 Bra	2 Brass 4 Galvanized steel 6				!	9 ABS	12 None used (open hole)			
SCREEN (OR PERFOR	RATION OPENIN	GS ARE:	5 Gau	zed wrapp	ed	8 Saw cut		11 None (ope	n hole)
1 Co	ntinuous slo	t (3) M	ill slot	6 Wire	wrapped		9 Drilled hole	s		
2 Lo	uvered shutt	er 4 Ke	ey punched	7 Toro						
SCREEN-F	PERFORATE	ED INTERVALS:	From	7.•0 ft. to	32.	. ⁰ ft., Fro	m	ft. t	o	ft.
				ft. to						
0	GRAVEL PA	CK INTERVALS:	From	5.5 ft. to	32.	5 ft., Fro	om	ft. t	o <i>.</i>	ft.
			From	ft. to		ft., Fro	m	ft. t	o	ft.
6 GROUT	MATERIAL	.: 1 Neat o	ement	2)Cement grout	(3)E	Bentonite 4	Other			
Grout Inter	rvals: From	m <u>0</u>	ft. to 3.	5 ft., From	3 . 5	ft. to 5 • 5	ft., From	. . <i></i>	ft. to	ft
What is the	e nearest so	ource of possible	contamination:			10 Lives	stock pens	14 A	bandoned wate	r well
1 Se	ptic tank	4 Later	al lines	7 Pit privy		11 Fuel	storage	15 O	il well/Gas well	
2 Se	wer lines	5 Cess	pool	8 Sewage la	goon	12 Fertil	lizer storage	(16) O	ther (specify be	elow)
3 Wa	atertight sew	er lines 6 Seep	age pit	9 Feedyard		13 Insec	cticide storage	Indust	trial Ware	house
Direction f	_	West	•	·		How ma	inv feet? 5			
FROM	то		LITHOLOGIC	LOG	FRO	м то		PLUGGING II	NTERVALS	
0	3.0	Light Br	own Lean S	Sandy Clay						
3.0	25.0	Light Br	own Medium	Sand with						
		Gravel								
25.0	29.5	Gray Coa	rse Sand a	and Gravel						
29.5	32.5	Green-Gr	ay Weather	ed Shale						
									-	
) =luc==-1	1a	
7 CONTR	RACTOR'S (OH LANDOWNER	CENTIFICATION OF A CO.	TION: This water well	was (1) co	nstructed, (2) reco	onstructed, or (3	piugged und	er my jurisaicti	on and was
)				best/ot my kn	owledge and be	ellet. Kansas
Water Wel	I Contractor	s License No		This Water			,	ر	1///	
	business na			Consultants,		by (signa		100	MARIL	
INSTRU	JCTIONS: Use to	pewriter or ball point	pen. PLEASE PRESS	S FIRMLY and PRINT clearly. 520-7320. Telephone: 913-296	Please fill in t	olanks, underline or circl	le the correct a sy	s. Sono top three	copies to Karisas De	partment