


1 LOCATION OF WATER WELL: <b>Sedgwick</b>		FRACTION <b>SE 1/4 SE 1/4 NE 1/4</b>		Section Number <b>34</b>	Township Number <b>T 27 S</b>	Range Number <b>R 1E E/W</b>
Distance and direction from nearest town or city street address of well if located within city? <b>1915 S. Chautauqua Wichita, KS.</b>						
2 WATER WELL OWNER: <b>CREDIT UNION OF AMERICA</b> RR#, ST. ADDRESS, BOX #: <b>229 Ellis</b> CITY, STATE, ZIP CODE: <b>Wichita, Kansas 67211</b> Board of Agriculture, Division of Water Resource Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL <b>23</b> ft. ELEVATION: Depth(s) groundwater Encountered <b>1</b> ft. <b>BASEMENT FLOOR</b> ft. <b>3</b> ft. WELL'S STATIC WATER LEVEL <b>12 1/2</b> FT. BELOW <b>1</b> AND SURFACE MEASURED ON <b>09/11/1992</b> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <b>X</b> No				
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded 7 Fiberglass Threaded Blank casing Diameter <b>1 1/4</b> in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <b>60</b> in., weight lbs. / ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATION INTERVALS: from ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: from ft. to ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <b>0</b> ft. to <b>8</b> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <b>South</b> How many feet? <b>10</b>						
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS <b>0 8 cement grout</b> <b>8 12 1/2 bentonite hole plug</b> <b>12 1/2 23 chlorinated sand and gravel</b>						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <b>09/11/1992</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <b>236</b> This Water Well Record was completed on (mo/day/yr) <b>09/25/92</b> Under the business name of <b>Harp Well &amp; Pump Service, Inc.</b> by (signature) <i>Jane Frederick</i>						

109