


1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 NE 1/4 Section Number 34 Township Number T 27 S Range Number R 10 E/W  
County: Sedgwick  
Distance and direction from nearest town or city street address of well if located within city?

1718 George Washington Blvd.  
2 WATER WELL OWNER: Town & Country ~~Market~~ Foods Market, Inc.  
RR#, St. Address, Box #: 1522 S. Florence Board of Agriculture, Division of Water Resources  
City, State, ZIP Code: Wichita KS 67209 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:   
4 DEPTH OF COMPLETED WELL: 32.5 ft. ELEVATION: 22.93 ft. below land surface measured on mo/day/yr 3-22-93  
Depth(s) Groundwater Encountered 1. 27 ft. 2. ft. 3. ft.  
WELL'S STATIC WATER LEVEL 22.93 ft. below land surface measured on mo/day/yr 3-22-93  
Pump test data: Well water was ft. after hours pumping gpm  
Est. Yield gpm: Well water was ft. after hours pumping gpm  
Bore Hole Diameter 8 in. to ft., and in. to ft.  
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
Blank casing diameter 2 in. to ft. Dia. in. to ft. Dia. in. to ft. Dia. in. to ft. Dia. in. to ft.  
Casing height above land surface Flush in. weight 703 lbs./ft. Wall thickness or gauge No. 154  
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)  
12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
SCREEN-PERFORATED INTERVALS: From 17.5 ft. to 23.5 ft. From ft. to ft.  
From ft. to ft. From ft. to ft.  
GRAVEL PACK INTERVALS: From 16.5 ft. to 23.5 ft. From ft. to ft.  
From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 16.5 ft. to 1 ft. From ft. to ft. From ft. to ft. From ft. to ft.  
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well  
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage  
Direction from well? SE How many feet? 130

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	9.0	Silt, Clayey			
9.0	14.0	Silty sand			
14.0	23.5	Sand, med grain, well sorted			
23.5	32.5	Silty sand, fine to med well sorted			
Flush mount waiver granted 12-10-92 for Town & Country MKB; KDHE 02087161 by Don Taylor					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-22-93 and this record is true to the best of my knowledge and belief. Kansas  
Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 3-23-93  
under the business name of GSI by (signature) Allison Inman