

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction SW SW NE 1/4 NW 1/4		Section Number 6	Township Number T 27 S	Range Number R 1 E/W
Distance and direction from nearest town or city street address of well if located within city? 2817 North Clarence Wichita, Kansas						EAST
2 WATER WELL OWNER: Mike Lendwehr RR#, St. Address, Box # : 2817 North Clarence City, State, ZIP Code : Wichita, Kansas				Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION:				
<div style="text-align: center;"><p>1 Mile</p></div>		Depth(s) Groundwater Encountered 1. 15 ft. 2. 15 ft. 3. 15 ft.				
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 8-30-84				
		Pump test data: Well water was 11 ft. after 8-30-84 hours pumping 11 gpm				
		Est. Yield 11 gpm: Well water was 11 ft. after 8-30-84 hours pumping 11 gpm				
		Bore Hole Diameter 11 in. to 11 ft., and 11 in. to 11 ft.				
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well				
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well						
Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted						
Water Well Disinfected? Yes X No X						
5 TYPE OF BLANK CASING USED:						
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X Clamped X		
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded X		
		7 Fiberglass		Cer-Mac styrene SDR-26 Threaded X		
Blank casing diameter 5 in. to 25 ft., Dia. 5 in. to 25 ft., Dia. 5 in. to 25 ft.						
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement				
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify) X				
		12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes						
		10 Other (specify) X				
SCREEN-PERFORATED INTERVALS: From 25 ft. to 40 ft., From 25 ft. to 40 ft., From 25 ft. to 40 ft.						
GRAVEL PACK INTERVALS: From 14 ft. to 40 ft., From 14 ft. to 40 ft., From 14 ft. to 40 ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 4 ft. to 14 ft., From 4 ft. to 14 ft., From 4 ft. to 14 ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)						
13 Insecticide storage						
Direction from well? West		How many feet? 85				
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	
0	2	Topsoil				
2	12	Clay				
12	19	Fine to Medium Sand				
19	28	Medium to Coarse Sand				
28	40	Coarse Sand and Gravel				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-30-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 2-1-85 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold						
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.						

OFFICE USE ONLY

T

R

END

SEC.

6

KSA 1/4 NE 1/4 NW 1/4