

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SW 1/4 NW 1/4 SW 1/4	29	T 27 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city? SAME AS OWNER					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		1015 STILLWELL WICHITA KS 67213			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 21.2 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 12.8 ft. 2. — ft. 3. — ft.			
		WELL'S STATIC WATER LEVEL 11.11 TC ft. below land surface measured on mo/day/yr 07-15-93			
		Pump test data: Well water was — ft. after — hours pumping — gpm			
		Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm			
		Bore Hole Diameter 7.25 in. to 2.5 ft. and — in. to — ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 <u>Monitoring well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted —			
		Water Well Disinfected? Yes — No X			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued — Clamped — 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded — Blank casing diameter 2 in. to 11 ft. Dia — in. to — ft. Dia — in. to — ft. Casing height above land surface 6L in. weight SC# 40 lbs./ft. Wall thickness or gauge No. — TYPE OF SCREEN OR PERFORATION MATERIAL: 7 <u>PVC</u> 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) — 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 <u>Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 11 ft. to 21.2 ft. From — ft. to — ft. SAND From 10 ft. to 25 ft. From — ft. to — ft. GRAVEL PACK INTERVALS: From — ft. to — ft. From — ft. to — ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other BENTONITE GROUT Grout Intervals: From 1 ft. to 9 ft. From 9 ft. to 10 ft. From — ft. to — ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage CONTAMINATED SITE					
Direction from well? — How many feet? —					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
6L	1.5	GRAVEL-CLAY - FILL			
1.5	5.5	SILTY SAND ZON -			
5.5	10	SAND - FINE MED - L FBN. -			
10	13	SAND - MED TO COARSE			
		ST AND DGR AND WATER 12.8			
13	25	SAND-MED TO COARSE			
* WATER RECOVER TO GREAT TO SLUG TEST					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07-13-93 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 07-29-93					
under the business name of EBBERTS DRILLING by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4